

FUJITSU

M4099D



A3 **DUPLEX**
DOCUMENT
SCANNER

- 1000pages
AUTOMATIC
- IPC-3D
Pre-Installed
- 32MB
- Dual InterFace
SCSI-2
RS232C+
Video
- Dropout
Color
Selectable
- Page
Counter
- Error
diffusion
- A3 Double
letter
- IBU
A3 ipm
- Duplex Scanning

QUALITY SCANNER

M4099D

TECHNICAL SPECIFICATIONS

The M4099D image scanner (dual interface model with RS232C+video interface and SCSI-2 interface) offers high speed, duplex scanning, and other excellent features, making it ideal for production scanning.

- High Performance
 - High-Speed Scanning
 - Simplex: 90 pages per minute (A4/200dpi)
 - Duplex: 180 images per minute (A4/200dpi)
 - Continuous Scanning
 - 1,000-sheet automatic document feeder improves operator productivity
 - 32MB pre-installed memory
- Drop-Out Color
 - The M4099D has Drop-Out Color features as a standard.
- Easy Separation Roller replacement
- Quality Results
 - Image Processing features (IPC 3D) pre-installed
 - Various Document Sizes
 - A7 to A3 or double letter (11 in. x 17 in.)
 - Manual Feeding Mode
 - Double Feed Detection
 - Long Page scanning (up to 30 in.)
 - Blank Page Detection
 - Quality resolution 400dpi
- Others
 - Page Counter
 - Grayscale Output
 - LCD panel
 - Slot for Optional Board
 - Endorser (Imprinting option)



Operating method		ADF (Duplex)
Image sensor		Color CCD (charge-coupled device) image sensor
Light source		White lamp
Document size		Minimum: A7 Maximum: A3 or double letter (11 in. x 17 in.)
Output resolution		400/300/240/200 dpi (selectable)
Scanning speed (mechanical)	Simplex scanning	90 ppm for A4 portrait format at 200 dpi
	Duplex scanning	180 ipm for A4 portrait format at 200 dpi
Grayscale level (internal)		256 levels image data processing in the scanner
Half-tone patterns		Dither; Error diffusion
Capacity of ADF		Maximum: 1,000 sheets, ream weight: 55 kg (117 lbs. 64 g/m ²)
Interface		SCSI-2/RS232C+Video/Third party slot
Video output format		Binary, half-tone, grayscale
Power requirements		100-240VAC, 50/60Hz
Power consumption		250VA or less
Operating environment		Temperature: 15°C-35°C (59°F-95°F) Relative humidity: 20% - 80% (noncondensing)
Dimensions (WxDxH)		588x689x540 mm (23.1x27.1x21.2 in.)
Weight		65 kg (143 lbs.)
IPC 3D (Image processing circuit 3D) pre-installed		1) IPC functions Dither pattern download Automatic binarization Automatic separation between photographs and text Zooming: 25% to 100% by 1% steps Outline extraction Image emphasis Mirror image Reverse image 2) DTC functions Spot noise removing Dynamic threshold Gamma curve correction Filtering Threshold curve selection Smoothing
Options		Endorser Unit 30 characters, A/N, sub-scan direction

Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative.
First edition, December 1999

North American contact:
FUJITSU COMPUTER PRODUCTS OF AMERICA, INC.
2904 Orchard Parkway,
San Jose, CA 95134-2009, U.S.A.
Phone: (1-408) 432-6333
Fax: 894-1709
HOME PAGE: <http://www.fcpa.com/>

FUJITSU CANADA, INC.
2800 Matheson Boulevard East,
Mississauga, Ontario L4W 4X5, Canada
Phone: (1-905) 602-5454 Fax: 602-5457
HOME PAGE: <http://www.fujitsu.ca/>

European contact:
FUJITSU EUROPE LTD.
2, Longwalk Road, Stockley Park,
Uxbridge, Middlesex UB11 1AB, England
Phone: (44-181) 573-4444 Fax: 573-2643
HOME PAGE: <http://www.fujitsu-europe.com/>

FUJITSU DEUTSCHLAND GmbH.
Frankfurter Ring 211,
80807 München, Germany
Phone: (49-89) 32378-0 Fax: 32378-100

FUJITSU ITALIA S.p.A.
Via Nazario Sauro, 38
20099 Sesto S. Giovanni (MI), Italy
Phone: (39-2) 26294-1
Fax: (39-2) 26294-201

FUJITSU NORDIC AB
Kung Hans Väg 12,
S-192 68 Sollentuna, Sweden
Phone: (46-8) 626-4500 Fax: 626-4588

FUJITSU ICL ESPAÑA, S.A.
Paseo de la Castellana 95, TORRE EUROPA 5
28046 Madrid, Spain
Phone: (34-1) 581-8000 Fax: 581-8300

FUJITSU FRANCE S.A.
1, Place des Etats-Unis, SILIC 310,
94588 Rungis cedex, France
Phone: (33-1) 4180-3680
Fax: 4180-3666

Australian contact:
FUJITSU AUSTRALIA LTD.
Fujitsu House 2 Julius Avenue
North Ryde N.S.W. 2113, Australia
Phone: (61-2) 9776-4555 Fax: 9776-4019
HOME PAGE: <http://www.fujitsu.com.au/>

Asian contact:
FUJITSU HONG KONG LTD.
10th Fl., Lincoln House, 979 King's Road,
Taikoo Place, Island East, Hong Kong
Phone: (852) 2827-5780 Fax: 2827-4724

FUJITSU KOREA LTD.
11th Fl., Korea financial center building.,
Yoido-Dong 23-6, Youngdeungpo-ku,
Seoul, Republic of Korea
Phone: (82-2) 3787-6000 Fax: 3787-6074
HOME PAGE: <http://www.fujitsu.co.kr>

FUJITSU COMPUTER (SINGAPORE) PTE. LTD.
20 Science Park Road #03-01, Tele Teck Park
Singapore Science Park II, Singapore 117674
Republic of Singapore
Phone: (65) 771-5555 Fax: 771-5588
HOME PAGE: <http://www.fsl.com.sg>

FUJITSU TAIWAN LTD.
8F, No.170 Hung Tai Center Bldg.,
Tun Hwan Rd., Taipei, Taiwan, R.O.C.
Phone: (886-2) 545-7700 Fax: 717-4644

FUJITSU SYSTEMS BUSINESS (MALAYSIA) BHD.
Fujitsu Plaza, 1A Jalan Tandang 204, P.O. Box
636 Jalan Sultan 46770 Petaling Jaya,
Selangor Darul Ehsan, Malaysia
Phone: (603) 793-3888 Fax: 793-0888

FUJITSU SYSTEMS BUSINESS (THAILAND) LTD.
12th Fl., Olympia Thai Tower,
444 Rachadapisek Road, Samsenrok,
Huay Kwang, Bangkok 10320, Thailand
Phone: (662) 512-6066 Fax: 512-6068

FUJITSU PHILIPPINES, INC.
2nd Fl., United Life Bldg., Pasay Road, Legaspi
Village Makati, Metro Manila Philippines
Phone: (63-2) 812-4001 Fax: 817-7576

FUJITSU LIMITED

Computer Products Business Group
4-1-1, Kamikodanaka, Nakahara-ku, Kawasaki-shi, Kanagawa-Ken 211-8588, Japan
Phone: (81-44) 754-8347 Fax: (81-44) 754-8348
FUJITSU HOME PAGE: <http://www.fujitsu.co.jp/hypertext/scanner/eng/>

Corporate Headquarters
6-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8211, Japan

©1999 FUJITSU LIMITED
Printed in Japan
BC0117-1S