

# Switches, Semi-Rotary and Moulded

## TECHNICAL DATA AND DIMENSIONS



List No. with Term'ls	List No. with Tags	Ideogram	Switching	Peak Amps.	Bush
S.565†† ‡	S.253††		S.P.M.-B.	3 at 250 V. ~	Standard
				4 at 110 V. ~	
				6 at 6 V. ≈	
S.566†† ‡	S.254††		S.P.C.-O.	2 at 250 V. ~	Standard
				3 at 110 V. ~	
				4 at 6 V. ≈	


†† SEE PAGES 178-179 FOR EQUIVALENT MOULDED TYPES

‡ Also available with tags accepting 250 series push-on connectors.  
Order as List No: ---/POT.

For Instrument knobs to fit, please see pages 36 - 57  
The shafts on these switches are flatted to accept Bulgin knobs fitting by grub screw only. Special versions to accept push-on knobs can be supplied to quantity orders.

### ACCESSORIES FOR ABOVE SWITCHES

List No.	Description
P./No. 8780	Circular Disc Escutcheon, printed 'ON' 'OFF' in BLACK, with circular band, on frosted aluminium; $\frac{1}{32}$ " 11.9 mm. $\varnothing$ central hole O.A. $\varnothing 1\frac{1}{8}$ " 41.3 mm. Fits under fixing nut of switch. For use with all semi-rotary switches above.



Switch with Part No: 8780 Dial and K.107/Knob added


## Switches, Slide Action

List No. with Terminals	List No. with Tags	Ideogram	Switching	Peak Amps.
S.590†††	S.591††		S.P.M.-B.	3 at 250 V. ~ 4 at 110 V. ~ 6 at 6-12 V. ≈
S.592†††	S.593††		S.P.C.-O.	2 at 250 V. ~ 3 at 110 V. ~ 5 at 6-12 V. ≈
—	S.594		D.P.M.-B.	1 at 250 V. ~ 1 at 110 V. ~ 1 at 6-12 V. ≈
—	S.596		D.P.C.-O.	1 at 250 V. ~ 1 at 110 V. ~ 1 at 6-12 V. ≈


‡ Also available with tags accepting 250 series push-on connectors.  
Order as List No: ---/POT.

†† SEE PAGES 178-179 FOR EQUIVALENT MOULDED TYPES.  
Escutcheon for above Slide Action Switches

Part No.	Description
8298	Polished Aluminium and Matt Black Finish



List No: S.591/POT  
Illustration showing AMP type tags available on some models.



Part No: 8298