

# Terminals

## L1005/1 Terminal

A heavy current terminal incorporating a non-rotating head for lettering. The rotating collar is captive and the clamping gap is free from threads.

**Current rating:** \_\_\_ 100 A

**Temperature range:** \_\_\_ -25 °C to + 85 °C (ambient)

**Materials:** \_\_\_ Head, phenolic resin  
Disc, tenite butyrate  
Stem, brass, nickel plated

**Colours:** \_\_\_ Head, black  
Disc, red or black

**Weight:** \_\_\_ 59,9 g average



L1005/1  
with H Fitting.

## H panel fittings

**Comprises:** Phenolic resin moulding. Micanite insulating washer. Metal washer. 2 locknuts

**Breakdown voltage:** \_\_\_ >4 kVd.c.

**Temperature range:** \_\_\_ -25 °C to + 85 °C

**Insulation resistance:** \_\_\_  $\geq 10^3$  megohms



**Panel thickness:** 1,6 mm to 23,8 mm

**Fixing torque:** \_\_\_ 2,8 Nm to 3,5 Nm

**Colour:** \_\_\_ Black

## Ordering reference: L1005/1/Colour H panel fittings

(Terminals and fittings are supplied unassembled and must be ordered as individual items.)



Panel cut-out