

CASA Assembly Instruction for:- "11BNC-PE-RG58-xxmm(HS)"

Assembly & Cable Preparation details for the following CASA Crimp Coaxial Connectors:-

Note - Double-screened cables RG-233 etc. may be used provided the single screen crimp ferrule is substituted with the DOUBLE screen part.


11BNC-50-3-RG58(J01000A1255)

or other brands subject to appropriate preparation dimensions.

11BNC-50-3-4(Suhner)

11BNC-50-3-RG58NT3Au(CASA) or other brands as approved by clients

$$\text{CUT Length} = \text{"CL"} = \text{OL} - 8.5\text{mm}$$



Installation Steps:-

- 1) Prepare Cable End to Drawing detail shown here
- 2) Fit HS ID Marker/labels and clear HS cover tubes
- 3) Fit and CRIMP centre pin onto centre conductor
- 4) Fit Ferrule (and Heatshrink/Taper Sleeve)
- 5) Clean and Inspect dielectric to contact interface
- 6) Flare Braid to receive spigot
- 7) Install Connector Body onto contact & cable
- 8) Slide Ferrule over Spigot & Braid
- 9) Crimp Ferrule with "2B" (5.5mm Hex) Orange Cavity
- 10) Install Heatshrink (or taper sleeve).
- 11) Heatshrink Sleeves and ID markers as appropriate

Schleuniger 207
Cable # xx (PE-RG58-cc)
Step 1 = xxx
Step 2 = xxx
Step 3 = xxx

Use the SUHNER "Orange" 75Z-0-3-4 (2B) Hand Tool or "Orange" Die-Sets 76Z-0-3-1 or 51 Crimp Cavity Size 1.6mm (0.063") square + 5.5mm (0.217") AF hexagonal for the Ferrule
The centre pin is crimped unless soldering is being specified by the customer.

CASA Modular Systems

P.O. BOX 38-828, WELLINGTON, NEW ZEALAND
TELEPHONE : (64-4) 9393 777
FACSIMILE : (64-4) 9393 778

CUSTOMER : CASA Modular Systems

DESCRIPTION : "11BNC-PE" Cable Assembly Instruction

DRAWN : AWD

DATE : 15/10/08

APPROVED : ?

DWG. SCALE : 1:1

SIZE : A4 DRAWING Reference No. : 11B-PE-RG58 ISSUE : A

COPYRIGHT : CASA Modular Systems ALL RIGHTS RESERVED

JOB No. : XXXX