



CABLES : ALPHA LIST

PO BOX 38-828, Petone
Phone 04-9393 777
FAX 04-9393 778

HEADING EXPLANATIONS :

Avail = Actual AVAILABLE stock for sale (include stock to arrive, stock in production, less customers forward order)
Un = Unit of supply / pricing (M = Metre, M2 = Square Metre, Kg = Kilogram etc.)
Price = List Price for 1 Unit in NZ\$ (quantity prices will be supplied based upon customer requirements)
TypeNo = CASA's Product reference number (either the manufacturers OEM Number or produced from CASA's Part Number Composer see separate chart/table for explanation of the rules and nomenclature)



Sunday, 5 December 2004
13:01:37

Cables : LOOK UP & ALPHA Listing

Page 1

Report Name:- CAB_LS1.RSL (01/12/04)AWD

	P2I	P3I	TypeNo	Description	Price	Un	Avail
1	W	WW	1423-YELLOW(1000FT)	#30 Gauge YELLOW Solid Silver Plated OFHC KYNAR on 1000' Plastic Spools	36.43	R	2
2	W	WW	1423-WHITE(1000FT)	#30 Gauge WHITE Solid Silver Plated OFHC KYNAR on 1000' Plastic Spools	36.43	R	2
3	W	WW	1423-RED(1000FT)	#30 Gauge RED Solid Silver Plated OFHC KYNAR on 1000' Plastic Spools	36.43	R	2
4	W	WW	1423-GREEN(1000FT)	#30 Gauge GREEN Solid Silver Plated OFHC KYNAR on 1000' Plastic Spools	33.12	R	2
5	W	WW	1423-CLEAR(1000FT)	#30 Gauge CLEAR Solid Silver Plated OFHC KYNAR on 1000' Plastic Spools	33.12	R	3
6	W	WW	1423-BLUE(1000FT)	#30 Gauge BLUE Solid Silver Plated OFHC KYNAR on 1000' Plastic Spools	36.43	R	2
7	W	SOL	22SWG-Ag-Sn-362P(0.25Kg)	0.7mm Ag/Sn 60/40 Solder (22SWG, 0.028") Multicore 362p Flux on 500gm Spools	44.25	R	5
8	W	SOL	22SWG-62/36/2(0.5Kg)	62/36/2 Silver Resin Cored Solder 0.5kg	42.00	R	0
9	W	SOL	22SWG-62/36/2(0.25Kg)	62/36/2 Silver Resin Cored Solder 0.25kg	26.25	R	0
10	W	SOL	22SWG-60/40(3Kg)	60/40 Resin Core Type 35 Solder 3kg	152.25	R	1
11	W	SOL	22SWG-60/40(0.5Kg)	60/40 Resin Core Type 35 Solder 0.5kg	24.50	R	5
12	W	SOL	22SWG-60/40(0.25Kg)	60/40 Resin Core Type 35 Solder 0.25kg	14.00	R	10
13	W	SOL	22SWG-362P-M4-RINGS	Solder Ring 4mm ID x 0.7mm 60/40 Solder (22SWG, 0.028") Multicore 362p Flux	0.96	H	129
14	W	SOL	22SWG-362P(0.5Kg)	0.7mm 60/40 Solder (22SWG, 0.028") Multicore 362p Flux on 500gm Spools	21.02	R	129
15	W	SOL	20SWG-60/40(3Kg)	60/40 Resin Core Type 35 Solder 3kg	143.50	R	1
16	W	SOL	20SWG-60/40(0.5Kg)	60/40 Resin Core Type 35 Solder 0.5kg	22.75	R	13
17	W	SOL	20SWG-60/40(0.25Kg)	60/40 Resin Core Type 35 Solder 0.25kg	12.25	R	10
18	W	SOL	18SWG-60/40(3Kg)	60/40 Resin Core Type 35 Solder 3kg	134.75	R	2
19	W	SOL	18SWG-60/40(0.5Kg)	60/40 Resin Core Type 35 Solder 0.5kg	21.00	R	-1
20	W	SOL	18SWG-60/40(0.25Kg)	60/40 Resin Core Type 35 Solder 0.25kg	12.25	R	5
21	W	SOL	18SWG-362P-M4.75-RINGS	Solder Ring 4.75mm ID x 1.2mm 60/40 Solder (22SWG, 0.028") Multicore 362p Flux	1.91	H	129
22	W	SOL	16SWG-60/40(3Kg)	60/40 Resin Core Type 35 Solder 3kg	134.75	R	0
23	W	SOL	16SWG-60/40(0.5Kg)	60/40 Resin Core Type 35 Solder 0.5kg	21.00	R	1
24	W	SOL	16SWG-362P	1.6mm 60/40 Solder (16SWG, 0.064") Multicore 362P Flux on 500gm Spools	18.68	R	49
25	W	SOL	13SWG-40/60	2mm 40/60 Solder (13SWG, 0.082") DLM Flux Cored (40% Tin, 60% Lead) on 500gm Spools	14.01	R	13
26	W	SOL	1.2mm	1.2mm 60/40 Solder (18SWG, 0.032") Multicore 362p Flux on 500gm Spools	19.11	R	7
27	W	RW	V105/1.0mm(Gr)	Green Appliance Wire 1mm 100m Reel	0.15	M	100
28	W	RW	7/0076(V)	Violet Remit Wire (0.2mm) on Wooden Drum	0.00	D	13
29	W	RW	5MMAVS-WH/YEL	Auto Cable 5mm (xx/0.32) 1.2rtAVS White/Yellow PVC (x00m Drums)	1.06	M	400
30	W	RW	50TH(Red)	Red Remit Wire 7/0.15mm 2000m Reels	0.10	M	2000
31	W	RW	50TH(BI)	Black Remit Wire 7/0.15mm 2000m Reels	0.10	M	2000
32	W	RW	50TH	Remit Wire 7/0.15mm White on Drum of 3000m	0.10	M	3000
33	W	RW	40MMAVS-BLK	Auto/Battery Cable 40mm (494/0.32) 1.2rtAVS Black PVC (100m Drums)	8.39	M	380
34	W	RW	15MMAVS-BLK/YEL	Auto/Battery Cable 15mm (171/0.32) 1.2rtAVS Blan/Yellow PVC (100m Drums)	2.93	M	80
35	W	RW	1.5MM(B)	Black Appliance Wire on 5000m Drums	0.34	D	3
36	W	RW	1.0mm(Gy)	Grey Appliance Wire on Reels of 150m	0.00	R	10
37	W	RW	1.0mm(B)	Brown Appliance Wire on Reels of 150m	0.00	R	8
38	W	RW	0.5mm(B)	Black Appliance Wire on 5000m Drums	0.00	D	3
39	W	RW	0.5MMAVF-BRN/YEL	Auto/Flexible Cable 0.5mm (20/0.18) 1.2rtAVS Brown/Yellow PVC (800m Drums)	0.53	M	800
40	W	RW	0.2mm(W)	White Remit Wire on Wooden Drum of 1500m	0.00	D	10
41	W	RW	0.1mm(Y)	Yellow Remit Wire on 500m Reels	0.00	R	4
42	W	RW	0.1mm(O)	Orange Remit Wire on 500m Reels	0.00	R	4
43	W	MW	MW-22AWG	22AWG Magnet Winding Wire	10.92	KG	23.4
44	W	MW	MW-2.65-G1	2.65mm Magnet Winding Wire	10.62	KG	7.2
45	W	MW	MW-1.60	1.60mm Magnet Winding Wire - Enamel/Polyurathene Insulated - on 20Kg plastic drums	8.49	KG	21.85
46	W	MW	MW-0.71-G1	0.71mm Magnet Winding Wire	7.10	KG	7.2
47	W	MW	MW-0.4	0.4mm Magnet Winding Wire	7.64	KG	4.5
48	W	MW	MW-0.34	0.34mm Magnet Winding Wire	8.19	KG	21.85
49	W	MW	MW-0.27	0.27mm Magnet Winding Wire	8.74	KG	732.55
50	W	MW	MW-0.25	0.25mm Magnet Winding Wire	9.28	KG	45.52



Cables : LOOK UP & ALPHA Listing

	P2I	P3I	TypeNo	Description	Price	Un	Avail
51	W	MW	MW-0.22	0.22mm Magnet Winding Wire	9.56	KG	25.63
52	W	MW	MW-0.12	0.12mm Magnet Winding Wire	12.29	KG	2.9
53	W	MW	MW-0.1	0.1mm Magnet Winding Wire	13.65	KG	69
54	W	MW	MW-0.09	0.09mm Magnet Winding Wire	15.02	KG	27.52
55	W	MW	MW-0.08-G1	0.08mm 0 Magnet Winding Wire	21.84	KG	0
56	W	MW	MW-0.06	0.06mm 0 Magnet Winding Wire	24.57	KG	3.1
57	W	MW	MW-0.04	0.04mm 0 Magnet Winding Wire	27.30	KG	2.36
58	W	HT	Assorted	High Temperature FibreGlass Insulated Aircraft Wires	0.00	M	0
59	W	BRAI	BRAID-337-13	Braid Tinned Copper 8mm nominal ID	8.60	M	75
60	W	BRAI	8/0.25-1C-PHC-PVC-YEL	Aerial Wire - 8x0.25mm Braided Hard-Drawn Copper with tough YELLOW PVC Jacket - 2mm OD on 500m steel drums	0.29	M	25000