



# D508/512

## High-Volume Desktop Printer



### Streamlined Features

- High Print Speed – up to 6 ips
- 305 dpi (203 dpi Optional)
- SATO and PCL-5 Compatible Programming Languages
- Cost Effective Direct Thermal Technology
- Easy View Media Window
- Clamshell Design
- High Lift Print Head
- USB Interface (standard)

### Industry Verticals

- Logistics
- Manufacturing
- Distribution
- Pharmaceutical & Healthcare
- Retail
- Transportation
- Apparel
- Automotive
- Military/DoD

### Industry Applications

- Pharmacy Labeling
- Wristband Printing
- Asset Labeling
- Retail Marking
- Shipping/Receiving
- Compliance Labeling
- Healthcare
- Product ID Labeling

# General Specifications

## D508/512

PRINTER MODEL		D508	D512
<b>PRINT SPECIFICATIONS</b>			
<b>Print Method</b>		Direct Thermal	
<b>Print Resolution</b>		203 dpi (8 dot/mm)	305 dpi (12 dot/mm)
<b>Print Speed</b>		6 ips (150 mm/second)	4 ips (100 mm/second)
<b>Max. Print Area</b>		4.1" (104 mm) W x 15.7" (400 mm) L	
<b>MEDIA SPECIFICATIONS</b>			
<b>Sensor Type</b>		Reflective Sensor (for use with pre-printed I-marks) See-Through Sensor (for die-cut label with gap) Sensor not used - Continuous	
<b>Media Type</b>		Roll and Fanfold	
<b>Media Size</b>	Width	1.1" (28 mm) - 4.65" (118 mm)	
	Length (Continuous)	0.71" (18 mm) - 15.75" (400 mm)	
	Length (Tear Off)	0.71" (18 mm) - 15.75" (400 mm)	
	Length (Cutter - opt.)	1.1" (23 mm) - 15.75" (400 mm)	
	Thickness	0.002" (0.06 mm) - 0.007" (0.19 mm)	
	Outer Diameter	4.33" (110 mm)	
	Inner Diameter	1.5" (40 mm)	
Wind Orientation		Face-out	
<b>FONT / SYMBOLOGIES</b>			
<b>Font</b>		U, S, M, WB, XS, XU, XM, XB, XL, OUTLINE, OCR-A, OCR-B, WL, CG Times, CG Triumvirate	
<b>Barcode Symbologies</b>	Linear	UPC-A, UPC-E, EAN-8, EAN13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128, RSS Composite Code	
	2-Dimensional	PDF417, Micro PDF417, Truncated PDF417, Maxicode, Data Matrix, QR Code	
<b>COMMUNICATION INTERFACE</b>			
<b>Interface Options</b>		IEEE1284, High-Speed, Bi-directional, Serial RS232 (up to 57.6k bps), Ethernet - 10/100BaseT (internal), Wi-Fi - 802.11b/g (internal), USB	
<b>OPERATING CHARACTERISTICS</b>			
<b>Power Requirements</b>		100-120 / 200-240 Volt AC (Jumper)	
<b>Environment</b>	Operating	32° to 95°F (0° to 35°C), 30-80% RH, non-condensing	
	Storage	23° to 140°F (-5° to 60°C), 30-90% RH, non-condensing	
<b>Dimension</b>		7.8" W x 9.1" D x 6.6" H (198 mm W x 230 mm D x 167 mm H)	
<b>Weight</b>		5.5 lbs (2.5 Kg) excluding AC adaptor	
<b>OPTIONS</b>			
Label Cutter (factory installed), Label Gallery Software			

\*Specifications subject to change without notice

### SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273  
 Phone: (704) 644-1650 Fax: (704) 644-1662  
 E-mail: sato-sales@satoamerica.com