

Coaxial PCB Connector 82_BMA-50-0-1/111_N

Description

Straight PCB jack

Interface Standards

IEC 60169-33_MIL-STD-348A/321



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|---------------------|---------------|
| Board mounting type | through holes |
| Weight | 0.001 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -65 °C to 125 °C |
| 2011/65/EC (RoHS) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Body | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00013034 |
| Catalogue drawing | DCA-00013236 |

Ordering Information

| | |
|----------------|----------------------|
| Single package | 82_BMA-50-0-1/111_NE |
|----------------|----------------------|

Remarks

PCB connector without stand-offs