



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 11_BNC-50-3-4/133_N

Description

Straight cable plug for flexible cable

SUHNER full crimp cable attachment



General Information

BNC Interface dims acc. to:
Weight:

IEC 60169-8_MIL-STD-348A/301_CECC 22120
0.0103 Kg / 0.36 oz

Cable

Cable type: RG_58C/U
Cable type: GX_03272

Cable Entry

Centre contact: crimped
Outer contact: crimped

Electrical Data

Impedance: 50Ω
Interface frequency max.: 4 GHz

Piece Parts

Center contact:
Outer contact:
Body:

Material

Brass
Brass
Brass

PFA / PTFE
Brass
MQ (Silicon Rubber)
Copper

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Insulator:
Coupling nut:
Gasket:
Crimp ferrule:

Attachments

Outline drawing: DOU-00006208
Assembly instruction: DOC-0000179061

Notes

Order as **11_BNC-50-3-4/133_NH** for Bulk 100 pcs

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 16.12.2003 19:20

Document: DOC-0000180965

RF_Ca_C_PDF

uncontrolled copy

Page 1



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>



SUHNER® COAXIAL CONNECTOR DATA SHEET

Order as **11_BNC-50-3-4/133_NE** for Single

WAIVER!
While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 16.12.2003 19:20

Document: DOC-0000180965

RF_Ca_C_PDF

uncontrolled copy

Page 2



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>