

HUBER+SUHNER® DATA SHEET

Coaxial PCB Connector: 85_BNC-75-0-1/133_N

Rev.: A



Description

Right angle PCB jack

Interface standards

IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance 75 Ω
Interface frequency max. 1 GHz

Mechanical Data

Board mounting type through holes
Weight 0.0152 kg

Environmental Data

Operating Temperature -65 °C to 165 °C

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator

Material

Copper Beryllium / Brass
Brass
Brass
PFA / PTFE

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00012866
Catalogue drawing DCA-00012868
Mounting hole DOU-00012084

Ordering Information

Bulk 100 pcs package 85_BNC-75-0-1/133_NH
Single package 85_BNC-75-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com