



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 11_716-50-7-2/003_-

Description

Straight cable plug for flexible cable

SUHNER full crimp cable attachment



General Information

7/16 Interface dims acc. to:
Weight:

IEC 60169-4_CECC 22190_DIN 47223_VG 95250
0.0842 Kg / 2.97 oz

Cable

Cable type: RG_214U
Cable type: GX_07272D

Cable Entry

Centre contact: crimped
Outer contact: crimped

Electrical Data

Impedance: 50Ω
Interface frequency max.: 7.5 GHz

Piece Parts

Center contact:
Outer contact:
Body:

Material

Brass
Brass
Brass

PFA / PTFE
Brass
MQ (Silicon Rubber)
Brass

Surface Plating

Silver Plating
Silver Plating
SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Insulator:
Coupling nut:
Gasket:
Crimp ferrule:

Attachments

Assembly instruction: DOC-0000179881

Notes

Order as 11_716-50-7-2/003_-E for Single

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 18.12.2003 17:37

Document: DOC-0000182473

RF_Ca_C_PDF

uncontrolled copy

Page 1



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>