


## 7-16 DIN Male Right Angle Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

**Product Description**

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications. The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.



OMNI FIT™ Standard Connectors

**Features/Benefits**

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

**Technical Specifications**

Transmission Line Type	Coaxial Cable
Cable Size	1/2"
Cable Type	Foam Dielectric
Model Series	LCF12-50 Series, ICA12-50 Series
Connector Interface	7-16 DIN
Nominal Impedance, ohms	50
Connector Type	OMNI FIT™ Standard Right Angle
Sealing Method	O-Ring
Gender	Male
Plating Outer/Inner	Trimetal/Silver
Length, mm (in)	60 (2.4)
Outer Diameter, mm (in)	48 (1.9)
Weight, kg (lb)	0.25 (0.55)
Inner Contact Attachment	Basket
Outer Contact Attachment	Spring O-Ring
3rd Order IM Product @ 2x20 Watts, dBc	-159 typical
Maximum Frequency, GHz	3.7
VSWR (Return Loss, dB)	0 < f = 1.0 GHz: 1.04 (34.1) 1.0 < f = 2.2 GHz: 1.07 (29.4) 2.2 < f = 2.7 GHz: 1.09 (27.3) 2.7 < f = 3.7 GHz: 1.13 ()
Wrench size front, mm (in)	24 (15/16)
Wrench size rear, mm (in)	24 (15/16)
Waterproof Level	IP68

**Notes****Other Documentation**

Installation instruction: [10000006026-05.pdf](#)

Application Note: [10000009163-01\\_Application Note\\_Installation of Heat Shrink Sleeves for additional sealing of Connectors.pdf](#)



7-16 DIN Male Right Angle Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

