



# SUHNER® COAXIAL CONNECTOR DATA SHEET

## TYPE 21\_716-50-7-2/003\_-

### Description

Straight cable plug for flexible cable



### *SUHNER full crimp cable attachment*

### General Information

7/16 Interface dims acc. to: IEC 60169-4\_CECC 22190\_DIN 47223\_VG 95250  
Weight: 0.0891 Kg / 3.14 oz

### Cable

Cable type: RG\_214U  
Cable type: GX\_07272D

### Cable Entry

Centre contact: crimped  
Outer contact: crimped

### Electrical Data

Impedance: 50Ω  
Interface frequency max.: 7.5 GHz

### Piece Parts

Center contact:  
Outer contact:  
Body:

### Material

Bronze / Brass  
Bronze  
Brass

### Surface Plating

Silver Plating  
Silver Plating  
SUCOPLATE (R) Plating

Insulator:

PFA / PTFE

Gasket:

NR (Natural Rubber)

Crimp ferrule:

Brass

SUCOPLATE (R) Plating

### Attachments

Assembly instruction: DOC-0000179881

### Notes

Order as **21\_716-50-7-2/003\_-E** for Single

#### WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 17.12.2003 17:46

Document: DOC-0000183638

RF\_Ca\_C\_PDF

**uncontrolled copy**

Page 1



**HUBER+SUHNER**

HUBER+SUHNER AG  
Interconnect Division  
CH-9100 Herisau  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
<http://www.hubersuhner.com>