

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_716-50-5-7/00-_-

Rev.: C



Description

Straight panel cable jack, flange mount

Interface Standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 7.5 GHz

Mechanical Data

Centre contact plugged
Outer contact soldered
Weight 0.1098 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Bronze
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

Surface Plating

Silver Plating
Silver Plating
Silver Plating

Related Documents

Outline drawing	DOU-00008763
Catalogue drawing	DCA-00008765
Assembly instruction	DOC-0000179355

Ordering Information

Single package 25_716-50-5-7/00-_-E

Additional Information

Suitable cable SUCOFORM_250

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions