

## SUHNER<sup>®</sup> COAXIAL CONNECTOR DATA SHEET **TYPE 16 N-50-3-15/133 N**

#### Description

Right angle cable plug for semi-rigid cable



#### **General Information**

N Interface dims acc. to: Weight:

Cable

# 0.0291 Kg / 1.03 oz

IEC 60169-16 MIL-STD-348A/304 CECC 22210

Cable type: Cable type: EZ 141-TP/M17 **SM 141PE** 

#### **Cable Entry**

**Electrical Data** 

Impedance: Interface frequency max .:

#### **Piece Parts**

Center contact: Outer contact: Body:

Insulator: Coupling nut: Gasket:

#### **Attachments**

Notes

Centre contact: Outer contact:

soldered soldered

Gold Plating (Nickel underplated)

**Surface Plating** 

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

**50**O 18 GHz

### Brass Brass

Order as

Order as

PFA / PTFE Brass MQ (Silicon Rubber)

Outline drawing: Assembly instruction:

16 N-50-3-15/133 NH

16 N-50-3-15/133 NE

DOC-0000179015

DOU-00005856

for Bulk 100 pcs for Single

**HUBER+SUHNER** 

HUBER+SUHNER AG Interconnect Division CH-9100 Herisau Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90 Fax http://www.hubersuhner.com

WAIVER While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 23.3.2004 12:55		Document: DOC-0000179014
RE Ca C PDE	uncontrolled copy	Page 1

Material Brass