# **Data Sheet**



# Coaxial Panel Connector 23\_N-50-0-33/133\_N

### **Description**

Straight panel receptacle jack, flange mount

Interface standards
IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \mbox{Impedance} & \mbox{50} \ \Omega \\ \mbox{Interface frequency max.} & \mbox{11 GHz} \end{array}$ 

**Mechanical Data** 

Number of matings 500
Weight 0.0248 kg

**Environmental Data** 

Operating temperature  $$-65\ ^{\circ}\text{C}$$  to 125  $^{\circ}\text{C}$$  2011/65/EU (RoHS) compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

#### **Related Documents**

Catalogue drawing DCA-00010811

## **Ordering Information**

Single package 23\_N-50-0-33/133\_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.