

SUHNER® COAXIAL CONNECTOR DATA SHEET **TYPE 32 N-50-0-1/133 N**

Description

Adaptor plug/plug



General Information

N Interface dims acc. to: Weight:

Electrical Data

Impedance: Interface frequency max .: Frequency range:

Piece Parts

Centre contact: Outer contact: Body: Insulator: Coupling nut: Gasket:

IEC 60169-16_MIL-STD-348A/304_CECC 22210 0.0557 Kg/ 1.96 oz

50Ω 11 GHz 0 ... 9 GHz

9 ... 12 GHz

Material

Brass Brass Brass

Surface Plating Gold Plating (Nickel underplated) SUCOPLATE (R) Plating SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

for Single

Brass MQ (Silicon Rubber)

Attachments

Notes

Catalogue drawing: DCA-00013682

Order as 32_N-50-0-1/133_NE

WAIVER! While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of



HUBER+SUHNER

HUBER+SUHNER AG Interconnect Division CH-9100 Herisau Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90 Fax http://www.hubersuhner.com

each product for any particular purpose must be checked beforehand with our specialists.		
Issued: 13.09.03 02:45		Document: DOC-0000194366
RF Ad W PDF	uncontrolled copy	Page 1