CASA Type #: 11PAL-75-5-RG6-EF125-YB DRAFT Suitable cables include industry standard 75 Ohm solid centre conducor types with 5mm solid or foamed dielectric with braided screens (with or without foil-wraps) RG-6/U + 15mm (cut-cable) add-on RG-6B/U for fitted connector other RG-6 types subject to testing. Optional Heat-Shrink SI; eeving 13mm ID coated or un-coated nominally 30~50mm long 19.0 37.5 12.5 Overall **₽** 21.30 **₽** Ø 11.00 7.0 RG-6 Types 75 Ohm Cables 7~8mm (nominal) OD MATERIAL 6.5 NΑ Max Cable 9.00 Preferred 12.0 ALLOY Ø 8.50 Crimp Zone NΑ 19.0 EST. AREA NΑ EST. WEIGHT EST.PERIPHER EXT: NA TDT: NA Connector Outline TOLERANCE 0.00mm ±0.1mm 00.00m ±0.1nm 00.0mm ±0.25mm 0000mm ±0.5mm 0-600mm ±0.1mm > 600mm ±0.5mm BS1474:1987 APPLIES UNLES OTHERWISE Recommended Hex Crimp Dies SPECIFIED 9.1mm AF X.X mm AF (nominally 8~9mm long) JOB No. 3000 CUSTOMER DRAWING Reference No. SIZE CASA Modular Systems 5 ☐ Modular Systems **A4** DESCRIPTION 11PAL-EF125RG6 Semi-Crimp PAL Plugs & Sockets from YuBright etc. Petone 5012, WELLINGTON, NEW ZEALAND C COPYRIGHT : CASA Modular Systems DWG. SCALE TELEPHONE : (64-4) 9393 777 DRAWN 27/05/19 APPROVED A.W.D ALL RIGHTS RESERVED WWW Address: www.casa.co.nz