



# SUHNER® COAXIAL CONNECTOR DATA SHEET

## TYPE 16\_SMB-50-2-23/111\_N

### Description

Right angle cable plug for semi-rigid cable



### General Information

SMB Interface dims acc. to:  
Weight:

IEC 60169-10\_MIL-STD-348A/311\_CECC 22130  
0.0038 Kg / 0.13 oz

### Cable

Cable type: EZ\_86-TP/M17

### Cable Entry

Centre contact: soldered  
Outer contact: soldered

### Electrical Data

Impedance: 50Ω  
Interface frequency max.: 4 GHz

### Piece Parts

Center contact:  
Outer contact:  
Body:

### Material

Copper Beryllium Alloy  
Brass  
Brass

### Surface Plating

Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)  
Gold Plating (Nickel underplated)

Insulator:

PFA / PTFE

### Attachments

Outline drawing: DOU-00008027  
Assembly instruction: DOC-0000179152

### Notes

Order as **16\_SMB-50-2-23/111\_NE** for Single

#### WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 16.12.2003 18:45

Document: DOC-0000183662

RF\_Ca\_C\_PDF

**uncontrolled copy**

Page 1



**HUBER+SUHNER**

HUBER+SUHNER AG  
Interconnect Division  
CH-9100 Herisau  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
<http://www.hubersuhner.com>