



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 11_TNC-50-7-2/133_N

Description

Straight cable plug for flexible cable



General Information

TNC Interface dims acc. to: IEC 60169-17_MIL-STD-348A/313_CECC 22200
Weight: 0.0397 Kg / 1.40 oz

Cable

Cable type: RG_213U
Cable type: RG_214U
Cable type: RG_393U

Cable Entry

Centre contact: soldered
Outer contact: clamped

Electrical Data

Impedance: 50Ω
Interface frequency max.: 11 GHz

Piece Parts

Center contact:
Outer contact:
Body:

Material

Brass
Brass
Brass

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Insulator:
Coupling nut:
Gasket:

PFA / PTFE
Brass
MQ (Silicon Rubber)

SUCOPLATE (R) Plating

Attachments

Outline drawing: DOU-00008068
Assembly instruction: DOC-0000179854

Notes

Order as **11_TNC-50-7-2/133_NE** for Single

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 18.12.2003 14:18

Document: DOC-0000183723

RF_Ca_C_PDF

uncontrolled copy

Page 1



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>