



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 22_TNC-50-0-2/133_N

Description

Straight bulkhead receptacle jack



General Information

TNC Interface dims acc. to:
Weight:

IEC 60169-17_MIL-STD-348A/313_CECC 22200
0.0079 Kg / 0.28

Electrical Data

Impedance:
Interface frequency max.:

50Ω
11 GHz

Piece Parts

Centre contact:
Outer contact:
Body:
Insulator:
Fastening nut:

Material

Copper Beryllium Alloy
Brass
Brass
PFA / PTFE
Brass
SUCOPLATE (R) Plating

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) PlatingWasher: Bronze

Attachments

00011568

Outline drawing: DOU-00011566

Catalogue drawing: DCA-

Notes

Mounting hole: DOU-00008762

Order as **22_TNC-50-0-2/133_NE**

for Single

WAIVER!
While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 10.11.03 14:47

Document: DOC-0000189571

RF_Pa_C_PDF

uncontrolled copy

Page 1



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>