HUBER+SUHNER® DATA SHEET Coaxial Panel Connector: 23_TNC-50-0-2/133_N



Description

Straight panel receptacle jack, flange mount

Interface standards IEC 60169-17 MIL-STD-348A/313 CECC 22200

Technical Data Electrical Data

 $\begin{array}{ll} \mbox{Impedance} & \mbox{50} \ \Omega \\ \mbox{Interface frequency max.} & \mbox{11 GHz} \end{array}$

Mechanical Data

Weight 0.0116 kg

Environmental Data

Operating Temperature -65 °C to 165 °C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts Material

Centre contact Copper Beryllium Alloy

Outer contact Brass
Body Brass
Insulator PFA / PTFE

Related Documents

Outline drawing DOU-00010312
Catalogue drawing DCA-00010314
Mounting hole ML6

Ordering Information

Single package 23_TNC-50-0-2/133_NE Bulk 100 pcs package 23_TNC-50-0-2/133_NH



Surface Plating

Gold Plating (Nickel underplated) SUCOPLATE (R) Plating SUCOPLATE (R) Plating

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com