

SUHNER® COAXIAL CONNECTOR DATA SHEET TYPE 34 TNC-50-0-1/133 N

Description

Bulkhead adaptor jack/jack



General Information

TNC Interface dims acc. to: IEC 60169-17_MIL-STD-348A/313_CECC 22200

Weight: 0.0195 Kg/ 0.69 oz

Electrical Data

 $\begin{array}{ll} \text{Impedance:} & 50\Omega \\ \text{Interface frequency max.:} & 11 \text{ GHz} \end{array}$

 Frequency range:
 0 ... 2 GHz
 2 ... 8 GHz
 8 ... 11

 Return loss:
 32 dB
 14 dB
 10 dB

 VSWR:
 1.05
 1.5
 1.9

Piece Parts Material Surface Plating

Centre contact:

Outer contact:

Brass

Body:

Copper Beryllium Alloy

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Insulator: PFA / PTFE

Gasket: MQ (Silicon Rubber)

Fastening nut. Brass SUCOPLATE (R) Plating Washer: SUCOPLATE (R) Plating

Attachments Outline drawing: DOU-00013573

Catalogue drawing: DCA-00013575

Notes Mounting hole: DOU-00008751

Order as **34_TNC-50-0-1/133_NE** for Single

WAIVER

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

each product for any particular purpose must be checked beforehand with our specialists.		
Issued: 10.11.03 17:13		Document: DOC-0000194152
RF_Ad_W_PDF	uncontrolled copy	Page 1



HUBER+SUHNER AG Interconnect Division CH-9100 Herisau Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 http://www.hubersuhner.com