

SA. 1861. Plug with Slit Pins left



The Pair List No. P.73

SA. 1862 with Solid Sockets right



SA. 468. Plug with Slit Pins left




The Pair List No. P.74

SA. 1988 with Solid Sockets right

Famous Bulgin Mains Inlet Connectors, moulded in highest commercial grades of phenolic material, normally BLACK. All metal parts are highly nickel-plated. In general, models have solid, tubular sockets (in SOCKET-members), and slit-pins (in PLUG-members), and terminals with 6 BA. pinch screws. Models with resilient-SOCKETS (and Solid-PINS) not for cross-mating, are now also listed, with solder-tag connections. Note, however, SA.1861-PLUG is also available with rear Tags. ORDER as SA.2190-PLUG (+SA.1862=P.73/RT) and SA.468-PLUG with rear tags becomes SA.2221 (+SA.1988=P.74/RT). Axial-entry All models have high current ratings, based on separation whilst carrying; as carrying-ratings the figures may be much higher.

Side Entry Plugs and Sockets, 5 Amp.



Plug: S.A.2096

List No: The Pair P.493




Socket: S.A.2097



Plug: S.A. 1861

List No: The Pair P.73/SE




Socket: S.A. 2111



Plug: S.A. 2341

List No: The Pair P.545



Socket: S.A. 2111

Female push-on connectors for S.A.2341 can be supplied if requested.

These models have side-entry for the cable on the flex-member and approved clamping for cable-grip. They are of the latest design, having conformity with modern specifications. One-piece electrodes (terminals integral with pins or sockets) that float, resilient sockets with solid pins wherever possible, and screws concealed whilst mated, for greatest safety, and highest ratings. Mouldings are of high grade phenolics, polished in appearance Connector P.493 (approved by G.P.O. and many Authorities, here and Overseas) also has versions with retention-lock and neon-glow. ("It glows whilst live") These are additional variations by means of different SOCKETS. (The PLUG remains common to all three versions). P.73/Side Entry mates with other P.73 versions; note the newest PLUG in this range fully cross mating, with Push-on tabs type male tags.