



S.A.1403. Plug with Solid Pins left




SA. 1393 with Slit Sockets right

The Pair List No. P.340




S.A.2020, Socket left



S.A. 2019, Plug right

The pair, List No: P.437

P.437 above and P.438 below are FACILITY OUTLETS, not Inlets. Accordingly it is the SOCKET or 'live' half and not the PLUG that is fixed, or apparatus, member.



S.A. 2026, Socket left



S.A.2025, Plug right

The pair, List No: P.438



Part No: 10450

New, screw-on, black moulded phenolic cover which enables the normally panel mounting socket SA. 2026 to be used as a flex-member

3-Pole Inlet

3-Pole 'Facility Outlets'

Further Mains Connectors for a wide field of applications. Mouldings are in glossy phenolic, highly polished, normally BLACK. As with most other Bulgin products, however, other colours can be moulded to quantity order, if previously agreed. Pins and Sockets are non-ferrous, highly Nickel-plated. The inlet model P.340 is for connecting and disconnecting the Mains-Lead at the Apparatus or Appliance itself. Widely used Domestically, and Professionally for Power and Lighting, and in Laboratories, especially where alternative portable apparatus is used selectively with common Mains-Lead, often made up as Laboratory fittings of differing lengths Plug has Solid Pins with Solder Tag connections and the Socket has Slit Sockets also with Solder Tag connections. The FACILITY OUTLETS allow 2-poles and Earth out of apparatus in subsidiary or auxiliary manner e.g. mains to dependent-unit and sub-unit, or to gram-motor, or similar. P.437, 6BA. terminals to both members; P.438 connections are soldered to either member. See left and right for accessories.