

Product data sheet Characteristics

PDL56PA520

Plug Angled, 56 Series, 20A 500V 3-Phase 5-Round Pin IP66, Orange





Main

Range	56 Series
Product or component type	Plug

Complementary

Rated current	20 A
[Ue] rated operational voltage	500 V
Material	Plastic
Colour tint	Orange
Surface finish	Gloss
Network frequency	50 Hz
Network number of phases	3 phases
Pin number	5
Ambient air temperature for operation	-4055 °C
Cable cross section	716 mm²
Quantity per set	Set of 4
Type of packing	Carton

Environment

IP degree of protection	IP66	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.0 cm	
Package 1 Width	9.0 cm	
Package 1 Length	17.0 cm	
Package 1 Weight	286 g	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

