

Product data sheet

Characteristics

PDL194E-23LC

Socket Assembly; 10A



Main

Range of product	PDL General Accessories
Product or component type	Socket-outlet
Colour tint	White
Quantity per set	Set of 25 Set of 800
Type of packing	Carton

Complementary

Material	PC (polycarbonate) Plastic
Surface finish	Glossy
[In] rated current	10 A
[Ue] rated operational voltage	240 V AC 50 Hz 230/240 V AC 50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Socket number	3
Installation direction	Vertical
Mounting support	Panel
Height	32 mm
Width	38 mm
Diameter	2.3 mm
Fixing center	38 x 32 mm
Connections - terminals	6.35 mm ² spade terminal






Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 cm
Package 1 Width	4.0 cm
Package 1 Length	5.2 cm
Package 1 Weight	17.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	400
Package 2 Height	24.0 cm
Package 2 Width	29.0 cm
Package 2 Length	33.0 cm
Package 2 Weight	6.8 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile