

Product data sheet

Characteristics

PDL570SWH

Single Square Flush Panel Mount Unswitched Shuttered Socket; 10A, 250V, White



Main

Range of product	PDL General Accessories
Product or component type	Socket-outlet
Colour tint	White

Complementary

Material	PC (polycarbonate)
Surface finish	Glossy
[In] rated current	10 A
[Ue] rated operational voltage	250 V 50 Hz
Network number of phases	1 phase
Socket number	3
Installation direction	Vertical
Height	50.8 mm
Width	50.8 mm


Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	5.3 cm
Package 1 Length	5.5 cm
Package 1 Weight	50 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration

RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile