

Niphan Flange Socket -Type B




LPA NIPHAN SYSTEMS



5 PIN + E

<250V

Niphan Flange Socket - Type B - Datasheet



		TEANOE GOOKET THE B					
			PART	DIMEN	ISIONS	FIXING	HOLES
PLANFORM	VOLTAGE	AMPS	NUMBER	D	Н	D	PCD
FLAMI OKWI	VOLIAGE						
	<50V	5	X2B/ODD	65	35	5	50.8
2 PIN	<250V	10	12B	65	38	5	50.8
	<230V	15	22B	65	50	5	50.8

FLANGE

SOCKET TYPE B

2 PIN + E	<50V	5	ХЗВ	65	35	5	50.8
	<250V	10	13B	65	38	5	50.8
		15	23B	65	50	5	50.8
	<500V	30	33B	65	59	5	50.8

	<250V	10	X4B	65	38	5	50.8
3 PIN + E	<500V	15	64B	65	54	5	50.8
	₹300 V	30	74B	65	59	5	50.8

<500V 15 65B 65 54 5 50.8	4 PIN + F	<250V	10	X5B	65	50	5	50.8
	46111176	<500V	15	65B	65	54	5	50.8

Х6В

65 50

20MM & 25MM SIZES

1	
	DESIGNED TO BE MOUNTED ON
	STANDARD BESA CONDUIT BOX

10

ASSOCIATED PRODUCTS						
GUARD						
RING	TRAILING	APPLIANCE				
PLUG	SOCKET	NLET				
PART	PART	PART				
NUMBER	NUMBER	NUMBER				
X2P/ODD	X2J	X2Q				
12S#	12J	12R				
22S#	22J	22R				
	·					

X3P	X3J	X3R
13S	13J	13R
238	23J	23R
33S	33J	33R

X4S	X4J	X4R
64S	64J	64R
74S	74J	74R

X5S	X5J	X5R
65S	65J	65R

X6S X6J X6R

LPA Niphan Systems makes every effort to ensure the accuracy of the information contained within this datasheet. However we reserve the right to withdraw and re-issue this datasheet at a later date.



5 50.8

LPA Niphan Systems Tudor Works, Debden Road, Saffron Walden, Essex, CBII 4AN Tel: +44 (0) 1799 512 800

Fax: +44 (0) 1799 512 828