



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 16_716-50-7-10/003_-

Description

Right angle cable plug for flexible cable



General Information

7/16 Interface dims acc. to:
Weight:

IEC 60169-4_CECC 22190_DIN 47223_VG 95250
0.1026 Kg / 3.62 oz

Cable

Cable type: RG_214U
Cable type: GX_07272D

Cable Entry

Centre contact: soldered
Outer contact: crimped

Electrical Data

Impedance: 50Ω
Interface frequency max.: 7.5 GHz

Piece Parts

Center contact:
Outer contact:
Body:

Material

Brass
Brass
Brass

PFA / PTFE
Brass
MQ (Silicon Rubber)
Brass

Surface Plating

Silver Plating
Silver Plating
Silver Plating

SUCOPLATE (R) Plating

Silver Plating

Insulator:
Coupling nut:
Gasket:
Crimp ferrule:

Attachments

Outline drawing: DOU-00006865
Assembly instruction: DOC-0000180803

Notes

Order as **16_716-50-7-10/003_-E** for Single

WAIVER! While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.		 HUBER+SUHNER HUBER+SUHNER AG Interconnect Division CH-9100 Herisau Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 http://www.hubersuhner.com
Issued: 18.12.2003 14:36	Document: DOC-0000180801	
RF_Ca_C_PDF	<i>uncontrolled copy</i> Page 1	