



UXP-DM-12



Mobile-enabled:
JMAqr.com



Scan for more info.

UXP-DM-12 DATA SHEET

7-16 DIN Male Connector
for 1/2" Annular Cables



Mechanical	Specification	Comment
Pull Force Combined	> 200 lbs .89 kN	Cable limited
Cable/Connector Torque	5 ft-lbs 6.7 N-m	Cable limited
Interface Durability	500 Cycles	

Electrical	Specification	Comment
Frequency Range	DC to 6 GHz	
Impedance	50Ω Nominal	
Average Return Loss (VSWR) DTF	> -40dB (1.02) 0-1 GHz, > -36dB (1.03) 1-2 GHz, > -32dB (1.05) 2-4 GHz, -28dB (1.08) 4-6 GHz	As per Anatel 75
Insertion Loss	< .1√F(GHz)	
3rd Order IMD	-153 dBc minimum, -160 dBc typical	As per IEC 62037-2, -3
Voltage Withstand	> 3.0 kV	
Shielding Effectiveness	< -120dB	0-1 GHz
Insulation Resistance	10GΩ initial, 100MΩ after conditioning	

Environmental	Specification	Comment
Operating Temperature/ Storage Temperature	-40°C to +65°C / -55°C to +85°C	
Interface Moisture	No leakage, mated or unmated > 1.0 Bar	
Moisture Ingress	No leakage	ANSI/SCTE60 2004, IP-67, IP-68, IEC 60529
Corrosion Resistance	1000 Hours	
H.A.L.T.	40 Hours	

General	Specification	Comment
Cable Supported	Andrew LDF4-50A, RFS LCF12-50, Draka RFA12-50, Leoni 1/2"R, Eupen EC4-50, Hansen 1/2", Rosenberger SL 012R FRNC	
Weight	0.311 lbs. 141.1g	
WPS Weather Protection	WPS-4A	
Length	2.120" 53.8mm	
Outer Diameter	1.040" 26mm	
Hex Width	1.25" 32mm	

Tools	Specification	Comment
Cable Preparation	SP-1/2-LDF4D	Bit "U", all cables
Connector Compression	HCG-FRAMESET-1/2, HCG-CC	Insert A
Torque Wrench	TQ-114-F18	18 ft-lbs 24.4 N-m

