

# Product data sheet

Specifications



modular buzzer iRO - 230 V  
50/60Hz - 70 dB

A9A15322

## Main

Range of product	Acti9
Product name	Acti9 iRO
Product or component type	Buzzer
Device short name	iRO

## Complementary

[Us] rated supply voltage	230 V AC at 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Net weight	64 g
Colour	White
Auxiliary connection terminal	Tunnel type terminalsrigid 4 mm² Tunnel type terminalsflexible 4 mm² Tunnel type terminalsflexible with ferrule 4 mm²
Wire stripping length	12 mm for bottom connection
Tightening torque	1.3 N.m

## Environment

Noise level	70 dB
Type of sound	Buzzer
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	8.2 cm
Number of Units in Package 1	1
Package 3 Width	30.0 cm
Package 3 Weight	9.115 kg
Package 2 Width	10.0 cm
Package 2 Height	8.3 cm
Package 2 Weight	715.0 g
Number of Units in Package 3	144
Unit Type of Package 3	S03
Package 3 Height	30.0 cm
Package 3 Length	40.0 cm
Package 1 Width	6.6 cm
Package 1 Height	1.8 cm
Package 1 Weight	55.0 g
Number of Units in Package 2	12
Unit Type of Package 2	BB1
Package 2 Length	22.8 cm

Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------