

L2004A; L2004A/F

Panel fuseholder
for size 0 fuse links

**SEMKO approved. VDE approved
UL Recognition**

Both L2004A and L2004A/F are fully finger-proof fuseholders having a special inner sleeve which prevents accidental contact when the fuse link is being inserted. They have been designed to meet the safety requirements of IEC 257 and BS415. Mounting on the panel is through a single hole shaped to engage the anti-swivel flats on the fuseholder.

They will accept either 6,3 x 0,81 mm or 4,75 x 0,81 mm solderless snap-on connectors. Supplied with a black removable bezel which snaps into place over the front flange.

L2004A is low profile and a coin slot in the head facilitates fuse link removal. L2004A/F has a raised head providing a fixing grip for fuse link removal.



L2003
Snap-on coloured
bezels



Snap-on bezels in green, grey, red and white can be supplied in packs of 50 quoting quantity of Belling-Lee reference and colour.

An adaptor, L1940A, allows 20 x 5 mm fuse links to be used in these fuseholders.

Current rating: _____	10 A (to IEC 257)
	15 A (Temperature rise to $\leq 40^\circ\text{C}$)
Breakdown voltage (d.c.): _____	> 4 kV
Temperature range: _____	-25°C to $+85^\circ\text{C}$ (ambient)
Insertion resistance: _____	5 milliohms (average)
Insulation resistance: _____	≥ 100 megohms
Panel thickness (maximum): _____	4 mm
Fixing torque: _____	1,2 Nm
Humidity: _____	21 days (BS2011 - IEC 68-1)
Material: _____	Glass filled polyester

Ordering reference: _____ **L2004A** **L2004A/F**
_____ **L2003/colour**

