

# L1055A

Size 0, standard  
glass fuse link  
32 mm x 6,3 mm  
(1 1/4 x 1/4 inch diameter)



These standard glass fuse links are for protection of telecommunications and light electrical equipment. They have a minimum life of 1,000 hours continuous rated current at 25 °C. They blow within 10 seconds at 2 x In (+ 20% to -0%). The derating for operation at elevated temperatures is: 1,75% per 10 °C up to 100 °C.

**Breaking capacity:** \_\_\_\_\_ 10 x In

**Voltage rating:** \_\_\_\_\_ See table below

**Markings:** \_\_\_\_\_ Rated value on cap

**Ordering reference:** \_\_\_\_\_ **L1055A/current rating in amperes**

## Current ratings:

Rating	Rated voltage	Rating	Rated voltage
60 mA	1,000 d.c. 250 a.c.	3 A	32 d.c. 150 a.c.
100 mA	1,000 d.c. 250 a.c.	5 A	32 d.c. 60 a.c.
150 mA	1,000 d.c. 250 a.c.	7.5 A	32 d.c. 60 a.c.
250 mA	750 d.c. 250 a.c.	10 A	32 d.c. 60 a.c.
500 mA	300 d.c. 250 a.c.	12 A	32 d.c. 60 a.c.
750 mA	300 d.c. 250 a.c.	15 A	32 d.c. 32 a.c.
1 A	250 a.c. 250 a.c.	20 A	32 d.c. 32 a.c.
1.5 A	200 d.c. 250 a.c.	25 A	32 d.c. 32 a.c.

