

BULGIN

Lamp Holders, Signal; Neon

MAINS NEON LEGEND SIGNAL LAMPS ON PAGES 102-103

RED AND GREEN LAMPS
All these Neon Signal Lamps can be supplied with GREEN NEONS (at slight extra cost) instead of normal RED, then lens fronts are Water-clear only. To obtain, add /GREEN NEON to List No.




List No: D.994/Volts
Neon and Resistor Assembly




List No: D.841/V Neon only




List No: D.808/V Neon only



List No: D.875/V Neon only



List No: D.712/V Neon only



List No: D.307/V

Neon Signal Lamps

A range of NEON Lampholders of various types, with series-resistor as tabled on right. The choice of models shown here will fully cover and meet all tastes and includes (top left) neon and resistor only assemblies, protected by heat shrink sleeving, for users having their own lens units. Applications are obvious on all domestic and professional apparatus, electric and electronic, private, industrial, or national. Extensively used in space-heaters, central-heating installations, kitchen and cooking equipment, etc., etc. Any neon is very easily fitted to show when apparatus is "five" or not, and consumption is only 1 1/2-2 mA. or less. No apparatus should be without at least one. All Neon Signal Lamps with built-in resistor are limited by the Resistor-Makers' rating to 100°C. max.


These fittings attach to panels by push-on nuts, spring tongues, screw-nuts or nuts and bolts, covering every convenient method. Modern NEONS (which we use exclusively) are "high-intensity" of brilliant glow, easily seen at a distance. We offer front lens caps in RED or WATER-CLEAR (the latter makes lit/un-lit contrast).

The latter can be used for giving "OFF" indication for two separate circuits, or a safety check on one circuit. Standard body colours are:


BULGIN

Lamp Holders, Signal; Neon


Colour Code:
BLACK Spot—110V.
RED Spot—250V.



List No: D.715/T Neon only



List No: D.715/V Neon only



List No: D.715/P.O.T./Colour



List No: D.740/V Neon only

List No.	For Glass Lenses add:	Panel Hole Ø	Bezel Ø	Max. Panel	Projection from Front of Panel	Lamp or Lamp Holder
D.808/110V./Colour		17/32" 13.5 mm	7/8" 22.2 mm	No Limit	Front 3/4" 19.1 mm Rear 1/2" 12.7 mm + Leads	
D.808/250V./Colour		1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.712/110V./Colour		9/16" 14.3 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.712/250V./Colour		1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.841/110V./Colour		9/16" 14.3 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.841/250V./Colour		1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.875/110V./Colour	Plastic only, Transparent Water-clear or Red	1/2" 12.7 mm	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	Neon inbuilt, with Resistor
D.875/250V./Colour		1/2" 12.7 mm	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.715/110V./Colour		1/2" 12.7 mm	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.715/250V./Colour		1/2" 12.7 mm	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.715/T/110V./Col.+	+ /T means 6 BA. terminals in place of solder tags	1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.715/T/250V./Col.+		1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.715/P.O.T./110V./Colour	/P.O.T. means tags to accept AHP push on connectors	1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.715/P.O.T./250V./Colour		1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.807/110V.		2-6 B.A. (ask for)	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	Twin neon inbuilt with
D.807/250V.		2-6 B.A. (ask for)	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.740/110V./Col.	Plastic, Transparent Red	1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	
D.740/250V./Col.	Water-clear, 1/2" 12.7 mm clearing	1/2" 12.7 mm clearing	19/32" 15.1 mm	3/4" 19.1 mm	Front 1/4" 6.4 mm Rear 1/2" 12.7 mm + Leads	