

BULGIN

Lamp Holders, Signal; Neon


MAINS NEON LEGEND SIGNAL LAMPS ON PAGES 102-103

RED AND GREEN LAMPS


All these Neon Signal Lamps can be supplied with **GREEN NEONS** (at slight extra cost) instead of normal **RED**, then lens fronts are **Water-clear** only. To obtain, add **/GREEN NEON** to List No.




List No: D.994/Volts
Neon and Resistor Assembly




List No: D.841/V
Neon only




List No: D.808/V
Neon only



List No: D.875/V
Neon only



List No: D.712/V
Neon only



List No: D.307/V

A very useful model conserves space. Combination of two separate window cut-outs. Ideal for applications where one neon is required and the other indicates when a secondary circuit is switched on. For example, when a fan is switched on, the neon is supplied with RED light at slight extra cost.

Neon Signal Lamps

A range of **NEON** Lampholders of various types, with series-resistor as tabled on right. The choice of models shown here will fully cover and meet all tastes and includes (top left) neon and resistor only assemblies, protected by heat shrink sleeving, for users having their own lens units. Applications are obvious on all domestic and professional apparatus, electric and electronic, private, industrial, or national. Extensively used in space-heaters, kitchen and cooking equipment, etc., etc. Any neon is very easily fitted to show when apparatus is "live" or not, and consumption is only 1½-2 mA. or less. No apparatus should be without at least one. All **Neon Signal Lamps with built-in resistor are limited by the Resistor-Makers' rating to 100°C. max.**


These fittings attach to panels by push-on nuts, spring tongues, screw-nuts or nuts and bolts, covering every convenient method. Modern **NEONS** (which we use exclusively) are "high-intensity," of brilliant glow, easily seen at a distance. We offer front lens caps in **RED** or **WATER-CLEAR** (the latter easies lit/un-lit contrast). This unique model has two lenses for giving "ON" or "OFF" indication for two separate circuits, or a safety check on one circuit. Standard body colour is **BLACK**, other colours

Lamp Holders, Signal; Neon
TECHNICAL DATA AND DIMENSIONS


BULGIN

List No.	For Glass Lenses add:	Panel Hole Ø	Bezel Ø	Max. Panel	Projection from Front of Panel	Lamp or Lamp Holder
D.808/110V./Colour		17/32" 13.5 mm	7/8" 22.2 mm	No Limit	Front 13.1 mm Rear 16.6 mm + Leads	
D.808/250V./Colour						
D.712/110V./Colour		1/2" 12.7 mm clearing	19/32" 15.1 mm	7/8" 22.2 mm	Front 11.1 mm Rear 21.4 mm + Leads	
D.712/250V./Colour						
D.841/110V./Colour		9/16" 14.3 mm	3/4" 19.1 mm	1/4" 6.4 mm	Front 6.4 mm Rear 34.9 mm + Leads	
D.841/250V./Colour						
D.875/110V./Colour	Plastic only, Transparent Water-clear or Red	5/8" 15.9 mm	23/32" 19.8 mm	1/4" 6.4 mm	Front 9.1 mm Rear 23 mm	Neon inbuilt, with Resistor
D.875/250V./Colour						
D.715/110V./Colour					Front 10.7 mm Rear 19.8 mm	
D.715/250V./Colour						
D.715/T/110V./Col.†	† /T means 6 BA. screw terminals in place of solder tags	16/32" 16.7 mm clearing	19/16" 20.6 mm x 1 1/16" 34.1 mm	3/4" 19.1 mm	Front 10.7 mm Rear 22.6 mm	
D.715/T/250V./Col.†						
D.715/P.O.T./110V./Colour	/P.O.T. means tags to accept 110 series AMP push on connectors					
D.715/P.O.T./250V./Colour						
D.807/110V.		2-6 B.A. c/sk h" @			Front 9.5 mm	Twin neons inbuilt with
D.807/250V.						
D.740/110V./Col.	Pla. Transparent Red Water-clear Also Amber	Clearing holes @ 1 1/2" 31.8 mm x 1/2" 12.7 mm	1 1/8" 31.8 mm x 1 1/8" 31.8 mm	7/8" 22.2 mm	Front 15.1 mm	
D.740/250V./Col.						


Colour Code:
BLACK Spot—110V.
RED Spot—250V.




List No: D.715/T/V
Neon only



List No: D.715/V
Neon only



List No: D.715/P.O.T./V
Colour



List No: D.740/V
Neon only