

PIBAOGU®

Flood light

Product Manual

120° beam angle, lighting area up to 200 square meters, can save you up to 80% on electricity bills compared with traditional halogen outdoor lights. HIGH QUALITY & LONG-LASTING: The exterior of the LED reflector is made of thickened ADC12 die-cast aluminum, which has better heat dissipation than other similar products and can provide you with a service life of up to 30,000+ hours.

Wide application: Can be used as outdoor floodlights for courtyards, parking lots, entrances, stadiums, basketball courts, etc. It can also be used as LED work lights in warehouses, factories, etc.

Easy to install: With the included screws to secure the adjustable metal bracket, you can install the LED security light on your outdoor wall, ceiling, or anywhere you want. Provide efficient lighting for your living environment and add extra security to your home.

Wiring instructions:

Red: Live wire

Blue: Natural wire

Yellow: Grounding wire

Technical Parameters

[Model]: leida-3、mini-2、HW-6、HW-7、PG-4、FJ-1、FJ-3、

FJ-4、FJ-6、FJ-7、FJ-8、PG-1、PG-2、PG-3

[Product power] 10W/20W/30W/50W/70W/100W/150W/200W/300W/
400W/500W/600W

[Material] Glass+Aluminum

[Rated voltage] 175-265V 50HZ/60HZ

[Rendering Index] >RA85

[Rated current] 0.08-4.8A

[Average lifespan] 50000 hours

[Color temperature] 2700K-6500K

[Full lighting effect] 90-101m/w

[Working temperature] -20-40℃

Non dimmable

Instruction Manual

made in China