





PDL 56 SERIES CHANGEOVER & REVERSING SWITCHES

Instructions for 56SW120C/O, 56SW320C/O, 56SW332C/O and 56SW320F/R


WIRING - REVERSING SWITCH: 56SW320F/R



WIRING - CHANGEOVER SWITCHES: 56SW120C/O, 56SW320C/O & 56SW332C/O



FITTING COVER MARKING LABELS



NOTE:
Before use
affix marking labels
to the cover

Cover options			

SPECIFICATIONS

IEC947/3	20A	32A
Rated Operation Voltage:	500V~	500V~
Rated Insulation Voltage :	Ui 690V~	690V~
Rated Thermal Current Enclosed:	ltthe 20A	32A
Rated Operational Current:	AC21A 500V le 20A	25A
(AC21A switching of resistive loads including moderate overloads)		

MOTOR RATING / OPERATIONAL POWER

Switching of motor loads or other highly inductive loads - AC23A		
AC23A	3 phase	380-500V
	1 phase	220-240V
Switching of squirrel cage motors - AC3		
AC3	3 phase	380-500V
	1 phase	220-240V
Terminal Capacities:		
	Stranded	2 x 2.5mm ²
	Flexible	2 x 2.5mm ²
		2 x 4mm ²
		2 x 4mm ²



New Zealand Head Office:
PO Box 15 355, New Lynn,
Waikato 0640, New Zealand
Telephone +64-9-829 0490, Fax +64-9-829 0491
www.pdl.co.nz




PDL Industries Australia Pty Ltd
Locked Bag 5500, Baulkham Hills Business Centre
Baulkham Hills NSW 2153 Australia
Freephone 1300 735 266, Direct 1300 735 329
Telephone +61 29851 2666, Fax: +61 29851 2695
www.pdl.com.au

PDL 56 SERIES CHANGEOVER & REVERSING SWITCHES





WIRING - REVERSING SWITCH: 56SW320F/R

Three Phase Reversing



56SW332C/O

LINE	LOAD	LOAD TERMINALS
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		
65		
66		
67		
68		
69		
70		
71		
72		
73		
74		
75		
76		
77		
78		
79		
80		
81		
82		
83		
84		
85		
86		
87		
88		
89		
90		
91		
92		
93		
94		
95		
96		
97		
98		
99		
100		



NOTE:
Before use
affix marking labels
to the cover

Cover options

UP ↑	AUX	MAN	REV 	I
OFF ○	OFF ○	OFF ○	OFF ○	OFF ○
DOWN ↓	MAIN	AUTO	FWD 	II

IEC947/3

IEC947/3 20A 32A

Rated Operation Voltage:	Ue	500V~
Rated Insulation Voltage :	Ui	690V~
Rated Thermal Current Enclosed:	Ithe	20A
Rated Operational Current:	AC21A 500V Ie	20A
(AC21A switching of resistive loads including moderate overloads)		

MOTOR RATING / OPERATIONAL POWER

Switching of motor loads or other highly inductive loads - AC23A	
AC23A	
3 phase	380-500V
1 phase	220-240V
	7.5kW (10hp)
	2.5kW (3.3hp)
	11kW (15hp)
	3kW (4hp)

Switching of squirrel cage motors - AC3	
AC3	
3 phase	380-500V
1 phase	220-240V
	5.5kW (7.5hp)
	7.5kW (10hp)
	2.2kW (3.0hp)
	3kW (4hp)

Terminal Capacities:	Stranded	2 x 2.5mm ²	2 x 4mm ²
	Flexible	2 x 2.5mm ²	2 x 4mm ²



New Zealand Head Office:
PO Box 15 355, New Lynn,
Waikare 0640, New Zealand
Telephone +64-9-829 0490, Fax +64-9-829 0491
www.pdli.co.nz



PDL Industries Australia Pty Ltd
Locked Bag 5500, Baulkham Hills Business Centre
Baulkham Hills NSW 2155, Australia
Freephone 1300 753 266, Freefax 1300 753 329
Telephone +61 29851 2666, Fax: +61 29851 2695
www.pdl.com.au

