

Home	Products	Search	Support	About Us
----------------------	--------------------------	------------------------	-------------------------	--------------------------

[Home](#) > [Search Engine](#) > Catalog: CSBLA480KEC8-B0

Resonators > CERALOCK (kHz) > Part Number







 How to check EU RoHS Compliance of Our Products is [here](#).

Product Lifecycle Stage	in Production
Recommended Rank	Preferred

Specifications

Global Part Number	CSBLA480KEC8-B0
Previous Part Number	CSB480E
Nominal Frequency	480.0kHz
Initial Tolerance	
Resonant Frequency	30ohm
Temp. Stability	±0.3%
Operating Temperature Range	-20 to +80•
Frequency Aging	±0.3%
Wash	Not Available
Ultrasonic Wash	Not Available
Built-in Load Capacitance	
Use	For consumer electronics

Details

-  [Part Numbering](#)
-  [Features and Applications](#)
-  [Temperature Characteristics](#)
-  [Basic Oscillation Circuit](#)
-  [Notice](#)
-  [Appearance/Dimensions](#)

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	500
Ammo Pack	
320Reel	
Magazine	
Box	

Please approve our product specifications or to transact the approval sheet for product specifications before

ordering.

Please read rating and !Cautions first.

Product specifications in this catalog are as of May 2011

Please make sure to read the Murata's [Product Policy](#) ,too.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP 

| [Site Map](#) | [History](#) | [Terms of use](#) | [Privacy Policy](#) |

All Rights Reserved, Copyright© Murata Manufacturing Co., Ltd.