KODAK EasyShare DX3900

Zoom Digital Camera





- 3.1MP image resolution for prints up to 28 x 36cm (11 x 14")
- 6X zoom (2X optical and 3X digital)
- Automatic and manual settings
- Removable COMPACTFLASH card (included)
- Compatible With the Kodak EasyShare Camera Dock

The high-performance camera

Picture-perfect

Being behind the camera is second nature. You love the creativity, the chance to capture the shot you'll be proud to print and share. The EasyShare DX3900 is for you. Thanks to 3.1MP resolution, you'll get excellent picture quality for prints up to 28 x 36cm (11 x 14"). Its 6X zoom (2X optical and 3X digital) lets you get closer to your subject for crisp detail.

Be in creative control

For the ultimate in creative freedom, set your own colour mode, ISO, and lighting exposure settings to get your perfect picture. The DX3900 comes with a COMPACTFLASH memory card. And with the DX3900's optional telephoto, wide-angle, and close-up lens attachments, you can extend your creativity.

Share with ease

If you use the optional KODAK EasyShare Camera Dock, sharing is just as easy. Place your DX3900 in the dock, touch the button, and your pictures are automatically transferred to your computer ready for e-mailing and printing. The Camera Dock will also recharge your camera's battery pack, so you'll always be ready to take more pictures.

The EasyShare System







KODAK EasyShare DX3900

Zoom Digital Camera



Built-in lens cover

Close-up, lighting, and exposure settings

Status light indicates picture transfer and battery charging

> Transfers pictures at the touch of a button

Quickly recharges your camera's battery pack

Great Picture Quality

CCD resolution 3.3 megapixel 3.1 megapixel, (2160x1440 pixels) image resolution 3.1MP low compressed 3.1MP high compressed 2.2MP, 1.6MP, 0.8MP image quality modes maximum 8 pictures at burst 0.8MP resolution 35 mm - 70 mm, f/2.8 - 4 lens/aperture range (35 mm equiv.), auto focus 6X (2X optical, 3X digital) zoom standard: 0.50m - infinity, focus distance (1.6 ft. - infinity) macro-wide: 0.07m - 0.7m (0.2 - 2.3 ft.) macro-tele: 0.25m - 0.7m (0.8 - 2.3 ft.) TTL-AE (multi-pattern, centre exposure control weighted, centre spot) 16 sec to 1/2000 sec shutter speed wide: 0.5 m - 3.2m flash range (1.6 - 10.5 ft.) tele: 0.5 m - 2.3 m (1.6 - 7.5 ft.) automatic, fill, red-eye, off flash mode 100 - 400 (automatic) ISO equivalent 100, 200, 400 (selectable) white balance automatic, daylight, tungsten, fluorescent colour mode black and white, sepia, colour self-timer 10 seconds JPFG file format Easy to Use viewfinder real-image optical viewfinder LCD 38 mm (1.5 in.) review/ preview colour display software KODAK Picture Software **Take More Pictures** Removable CompactFlash storage memory card Share Pictures Faster

digi

For more information on the KODAK

visit www.kodak.co.uk/go/easyshare

EasyShare Cameras with Camera Dock

digital still print marking	DPOF printing
interface	USB, KODAK EasyShare Camera Dock
video out	NTSC, PAL (user-selectable)

Other Specifications certification

tripod mount power options weight dimensions warranty

Power power/recharging

battery pack

input voltage System Requirements

WINDOWS:

WINDOWS 98, 98SE, 2000, ME or XP Personal computer with 200 MHz processor or greater 48MB minimum RAM (WINDOWS 98, 98SE, ME) 64MB minimum RAM (WINDOWS 2000, XP) 270MB hard drive disk space available CD-ROM drive Available USB port Colour monitor, 800x600 pixels (16-bit or 24-bit recommended) MACINTOSH: PowerPC-based MACINTOSH Computer

MACINTOSH OS 8.6/9.x/X

64MB RAM available

100MB hard drive disk space available

CD-ROM drive

Built-in USB port

Colour monitor, 800x600 pixels (thousands or millions of colours recommended)

Number of images from 8MB memory		
Quality mode	No. of images	
3.1MP Low Compression	7	
3.1MP High Compression	15	
2.2MP	10	
1.6MP	13	
0.8MP	23	



FCC Class B, ICES-003 Class B, CE, VCCI, C-tick

Optional Camera Dock with

Ni-MH rechargeable battery

pack (in-camera charging); 2AA Ni-MH rechargeable;

2AA Lithium batteries or

1CRV3 Lithium battery

WxHxD: 116x67x42 mm

permits battery charging in camera while docked, DC

power supply to camera

rechargeable battery pack

1.2 volt x 2 Ni-MH

7+/-0.7 volts DC

without batteries:

225 g (7.9 oz.)

(4.6x2.6x1.7 in.)

one year

(included)

standard

Includes removable CompactFlash memory card

Colour LCD display to preview and review your pictures

Burst mode

Colour, Black and White, and Sepia settings

Compatible with optional lens attachments

Package Contents

- ■KODAK EasyShare DX3900 Zoom Digital Camera with wrist strap
- KODAK Picture Software CD
- Cables for USB and video
- Removable CompactFlash memory card
- KODAK CRV3 Lithium battery or equivalent
- ■KODAK Ni-MH Rechargeable Battery Pack
- Insert for optional KODAK EasyShare Camera Dock Documentation kit

CAT No.

Ordering Information

Ordering Information	CAT No.
KODAK EasyShare DX3900 Zoom Digital	Camera
English/French/German8	
Spanish/Italian/Portuguese1	55 8220
Nordic/Dutch	332 2174
Recommended Accessories	
KODAK Lens Adaptor (32-37 mm)	176 2269
Close-up Lens Kit (37 mm threads) (Lens adaptor required)	138 2175
Wide-Angle Lens (0.5X-37 mm threads) (Lens adaptor required)	
Telephoto Lens (2.0X-37 mm threads) (Lens adaptor required)	179 2860
KODAK EasyShare Camera Dock and Ni-M rechargeable Battery Pack	
English/French/German1	18 3094
Spanish/Italian/Portuguese	313 3696
KODAK COMPACTFLASH Cards 32MB	140 4169 312 6187
KODAK Picture Launch (USB Compact Fla Reader/Writer)	sh Card 85 6346
KODAK Ni-MH Rechargeable Battery Pack with Camera Dock)1	(for use 85 3209
KODAK Rapid Battery Charger (for use wit Ni-MH Rechargeable Battery Pack	h KODAK
UK	898 0542
EAMER1	57 2908
KODAK Camera Bag	.114 7321

KODAK Accessories help make these great cameras even better. See your local retailer or visit us at www.kodak.co.uk/go/shop





he best results from tures, look for soft ng the KODAK Picture signation

©Eastman Kodak Company, 2002. Kodak, Share Moments. Share Life., EasyShare, and the KODAK Picture Friendly logo are trade marks of Eastman Kodak Company. GT 8666/02/02