



PAC-15AV (S40972) **PAC-171AV** (S73875) **& PAC-191AV** (S74629)

PACOM 15", 17" & 19" LCD Monitors

Key Features

- Industrial Case Design, aesthetically pleasing, making it ideal for Industrial or commercial applications.
- Sharp and clear images
- LCD Protective Glass
(PAC-171AV and PAC-191AV)
- Additional Inputs for security and industrial applications requiring multiple input and outputs (BNC type) with Audio, S-Video and RGB.
- High performance Image Processing Circuit. 3D Comb filter and Deinterlace function provides high quality images. (PAC-171AV and PAC-191AV)
- Unique stand. The stand allows for easy cable management and wall mounting

Specifications

LCD Monitor Model		PAC-15AV (S40972)	PAC-171AV (S73875)	PAC-191AV (S74629)
Display	Screen Size	15"	17"	19"
	Viewing Area	304.1 x 228.1 mm	338.0 x 270.0 mm	376.0 x 301.0 mm
	Pixel Type	Active Matrix TFT	Active Matrix TFT	Active Matrix TFT
	Max. Resolution	1024 x 768 @ 60Hz	1280 x 1024 @ 75Hz	1280 x 1024 @ 60Hz S-XGA
	Pixel Pitch	0.297 x 0.297 mm	0.264 x 0.264 mm	0.264 x 0.264 mm
	Brightness	250cd/m ²	300cd/m ²	300cd/m ²
	Contrast Ratio	450:1	1000:1	700:1
	Aspect Ratio	4 : 3	5 : 4	4 : 3
	Viewing Angle(H/V)	150°/135°	160°/160°	150°/135°
	Display Colour	16.2 Million	16.2 Million	16.7 Million
	Response Time	12ms	5ms	< 8ms
	Video System	NTSC / PAL	NTSC / PAL	NTSC / PAL
Audio	Frequency(H)	31 ~ 48 KHz (H)	31 ~ 64 KHz (H)	31 ~ 64 KHz (H)
	Frequency(V)	50 ~ 75Hz (V)	50 ~ 75 Hz (V)	50 ~ 75 Hz (V)
Interface	Built in Speakers	Yes (2W X 2)	Yes (2W X 2)	Yes (2W X 2)
	Gradual Volume Increase	YES	YES	YES
Interface	Video In/ Out (BNC Type)	2 / 2	2 / 2	2 / 2
	S-Video In/ Out	1 / 1	1 / 1	1 / 1
	RGB In (15Pin D-Sub)	1	1	1
	Audio In	2	2	2
	PC Stereo In	1	1	1
Transmitter	Remote Control	Yes	Yes	Yes
	Filter Type	2D Combfilter	3D Combfilter / DeInterlace	3D Combfilter / DeInterlace
	LCD Protection Glass	Not Available	Yes	Yes
	Multi-lingual Language	English, Spanish, French, German, Italian	English, Spanish, French, German, Italian	English, Spanish, French, German, Italian
	VESA™ DDC Compatible	Yes	Yes	Yes
Dimensions	Outline Dimension (With Stand)	380 x 385 x 190 mm	382.4 x 390.5 x 200 mm	430 x 428 x 200 mm
	Outline Dimension (Without Stand)	380 x 327 x 55 mm	382.4 x 330 x 58.7 mm	430 x 371 x 58.7mm
	Packaging Dimension	436.8 x 475 x 226 mm	436.8 x 475 x 226 mm	500 x 515 x 240 mm
	Net Weight	3.70Kg(8.16lbs)	5.94Kg (13.1lbs)	6.61Kg(14.6lbs)
	Gross Weight	5.70Kg(12.56lbs)	7.66Kg (16.9lbs)	8.43 Kg (18.6lbs)
Cabinet	Finish/Tilt Stand	Black/Yes	Black/Yes	Black/Yes
Mounts	VESA Mounts Size	100 x 100 mm (BS M4 x 10 mm Screw)	100 x 100 mm (BS M4 x 10 mm Screw)	100 x 100 mm (BS M4 x 10 mm Screw)
Regulations		TUV-NRTL (=UL), CB, FCC (A), CE-Emc (LVD)	TUV-NRTL (=UL), CB, FCC (A), CE-Emc (LVD)	TUV-NRTL (=UL), CB, FCC (A), CE-Emc (LVD)
Power	Consumption : < On	< 36W	< 36W	< 36W
	Electrical Ratings	AC100 ~ 240V (50/60Hz) DC 12V / 3A	AC100 ~ 240V (50/60Hz) DC 12V / 4.12A	AC100 ~ 240V (50/60Hz) DC 12V / 4.12A
Circumstance	Operating Temperature	0 ~ 40°C / 50 ~ 104°F	0 ~ 40°C / 50 ~ 104°F	0 ~ 40°C / 50 ~ 104°F

Available from:



Pacific Communications
CLOSED CIRCUIT VIDEO SYSTEMS

www.pacom.com.au



DIRECT ALARM SUPPLIES

www.das.com.au

