



HF/50MHz ALL MODE TRANSCEIVER

IC-7600

The Flagship's Lineage



Pushing performance to the pinnacle

The latest DSP technologies developed for the IC-7800/7700 plus over 45 years of analog circuit expertise give the IC-7600 the performance advantage.

The flagship's lineage: dual DSP units, 3kHz 1st (roofing) filter, double-conversion superheterodyne, all direct descendants of the IC-7800/7700.

Dual DSP



Separate DSP units for transmitter/receiver and spectrum scope.

Receiver System



The double-conversion superheterodyne system and the image rejection mixer improve inband IMD.

1st IF Filter



Three built-in 1st IF (roofing) filters: 3, 6 and 15kHz.

HF/50MHz ALL MODE TRANSCEIVER
IC-7600



Display

5.8-inch WQVGA (400×240 pixel)
ultra-wide viewing angle
TFT display with long-life
LED backlighting.



Spectrum Scope

High-resolution real-time spectrum
scope using a dedicated DSP unit.




USB Connectors

Easily connect keyboards,
flash memory drives, and PCs.



PSK Operation

Built-in PSK and RTTY operation
with a USB keyboard
- PC not required.



Receiver Performance Inherited from the Flagship

Rec

Dual DSP for transmitter/receiver and spectrum scope

Two separate 32-bit DSP units power the transmitter/receiver and spectrum scope. These processors give the IC-7600 high performance comparable to our top-of-the-line IC-7800 and IC-7700, thanks to the combination of dual DSP and our analog RF design expertise.




DSP unit for Transmit and Receive
TMS320C6726B (Top in photo)
Internal clock speed: 266MHz
32-bit floating point DSP
Maximum performance =1600MFLOPS

DSP unit for Spectrum scope
TMS320C6720 (Bottom in photo)
Internal clock speed: 200MHz
32-bit floating point DSP
Maximum performance =1200MFLOPS


104dB dynamic range and +30dBm third-order intercept point (IP3)

Icom's long years of analog RF circuit experience combined with the latest digital technology results in an astonishing 104dB receiver dynamic range and +30dBm IP3 in the HF bands without sacrificing receiver sensitivity. Even a weak signal adjacent to strong signals is clearly received by the IC-7600.





Double-conversion superheterodyne dramatically improves inband IMD

The IC-7600 employs a double-conversion superheterodyne system which has an image rejection mixer for the 2nd mixer stage. When compared to a typical triple-conversion system, the double-conversion system is more difficult to implement but it dramatically reduces signal distortion and provides a high-fidelity RF signal to the DSP processor.




Receiver System



Dual AGC loops controlled by DSP


The IC-7600 has dual AGC loops, one analog and one digital, both under DSP control. This architecture prevents strong adjacent signals from "pumping" the AGC and allows maximum dynamic range in the DSP.

AGC loop management



Three built-in 1st IF (roofing) filters, including 3kHz


The IC-7600 has three built-in 1st IF (roofing) filters ahead of the 1st IF amplifier stage. The 3kHz filter is especially effective in CW and SSB modes to eliminate overloading caused by strong signals just outside the passband.



6kHz, 3kHz and 15kHz 1st IF filters (from top to bottom)

Digital IF filter

The IC-7600 DSP allows you to "build your own" digital IF filter. You can quickly choose bandwidth, shape factor, and center frequency, so that you can work that rare DX station while your competition's still tweaking their transceiver controls. Three filter memories allow you to change filter settings instantly, a great help during contesting or other high-rate operating.



Digital IF filter setting example

Receiver performance standards all DX'ers have come to expect




Above photo includes optional SP-23 and IC-PW1/EURO.

Digital twin PBT

After "building your own" digital IF filter, you can use digital twin Passband Tuning (PBT) to shift and narrow the IF passband until the interference is gone and you can clearly hear that weak signal.

Digital notch filter


Signals such as heterodynes and AM carriers can be eliminated with automatic notch filter technology, making interference from RF sources such as beat signals and RTTY signals a thing of the past. You can also choose three shape factors for the notch filter, to optimize interference rejection.



Noise reduction

The processing power of the 32-bit DSP produces results you can hear! The 16-step variable noise reduction can significantly enhance the receiver's signal-to-noise ratio, giving you a clean, clear audio signal that may make the difference between making the contact or not.

Noise Reduction Characteristics




Noise blanker

A 100-step digital noise blanker reduces interference from pulse-type noise sources such as engine ignition systems.

Dualwatch function

Dualwatch allows you to receive two signals in the same band simultaneously. For example, you can listen to a DX station transmitting on 14.025MHz while also listening to the pileup calling him on 14.030MHz.

Dualwatch receiver (Same band only)



High stability TCXO unit

The IC-7600 provides ± 0.5 ppm frequency stability using a high stability temperature-compensate crystal oscillator (0°C to $+50^{\circ}\text{C}$). This high stability TCXO unit offers stable operation even during continuous transmission on RTTY or PSK31 mode.



TCXO Unit

Versatile Functions and Intuitive Operation

5.8 inch ultra-wide viewing angle TFT display

The IC-7600's ultra-wide viewing angle display has excellent color rendition and high contrast ratio with fast response time. These features allow the spectrum scope and simulated analog meters to move smoothly and naturally. White LED backlighting offers faster start-up, stable brightness, and very long life.



400×240 pixels,
130.2×68.9mm large display



Ultra-wide viewing angle display

Photo taken with room light turned off.

LCD and backlight Comparison between IC-7600 and IC-756PROIII*

		IC-7600	IC-756PROIII
LCD	Size	5.8 inch WQVGA	5 inch QVGA
	Viewing Angle	180° (approx.) (Horizontal/Vertical)	90° (approx.) (Horizontal) 60° (approx.) (Vertical)
Backlighting	Type	LED (White)	CCFL (Cold cathode fluorescent lamp)

*These specifications show the specifications of the individual devices only.

Spectrum scope

The dedicated spectrum scope DSP with built-in digital filtering greatly improves dynamic range, response time, and frequency accuracy of the spectrum scope. The scope automatically selects the optimum resolution based on the sweep bandwidth. In addition, the spectrum scope range can be set independently from the receiving frequency. You can monitor band conditions between the selected sweep edges (Max. 500kHz) in the fixed mode, as well as sweep a selected band width centered on the receiving frequency in the center mode.



Fix mode screen



DSP unit for spectrum scope

Digital voice memory

With digital voice memory, you can record the incoming signal and immediately replay the audio, a must-have feature for DXing and contesting. Because the transceiver is recording continuously, time-shift playback can replay the 15 seconds of audio that you heard <before> you pushed the Rec button!

The IC-7600 has a 4 channel transmit memory (maximum 90 seconds per channel) and 20 channel receive memory (maximum 30 seconds per channel, total 200 seconds with 20 channels). In addition, the recorded incoming signal can be saved on a USB flash drive.

TX MEMORY	VOICE RECORDER
1 21.200.00 USB	12- 2 11:22 8s
2 50.110.00 USB	12- 2 11:28 10s
3 14.210.00 USB	12- 2 11:24 15s
4 14.120.00 CW	12- 2 11:23 15s
5 7.076.00 CW	12- 2 11:22 21s

Digital Voice Recorder



Voice memory buttons

Multi-function meter

The multi-function meter allows you to observe the transmit/receive conditions at a glance.

In addition to the signal strength, transmit power level, ALC, compression level and SWR meters, the IC-7600 shows the drain terminal voltage of the final amplifier (Vd), the drain current of the final amplifier (Id) and temperature of the PA circuit (TEMP).



Multi-function meter setting screen

RF speech compressor

The digital RF compressor boosts average RF output power, improving signal strength and readability.

RTTY/PSK31 operation with a USB keyboard

Simply plug in a USB keyboard to operate RTTY and PSK! The digital twin-peak filter greatly reduces interference and a tuning indicator helps you zero-beat the signals. Eight RTTY and PSK transmit memories store up to 62 characters per channel.

Triple band stacking register

The triple band stacking register quickly memorizes and calls up the operating frequency and mode for 3 channels on each band. Just push the band key button (ten-key pad), and you can call up the last operating frequency and mode. This function is convenient especially when switching bands during contests, etc.

Programmable band edge beep

You can program the band edge not only according to the amateur radio band plan but also more specific frequencies like contest frequencies, CW operating mode, etc. If you try to operate on the OFF band, the transceiver alerts you with a beep sound. You can also inhibit transmitting in the OFF band.

Built-in memory keyer

Built-in memory keyer provides 4 channels for CW mode and 8 channels each for RTTY and PSK31 modes, capable of storing up to 70 characters for each channel. The memory keyer is useful for sending CQ or exchanging numbers during contests. When not contesting, you can store and send your name, QTH, rig, etc. With a USB keyboard, you can send memory contents using a function key on the keyboard.



Memory keyer screen

USB connectors on the front and rear panel

The IC-7600 has one USB connector on the front panel and one on the rear panel. You can connect a USB keyboard or USB flash drive to the front panel (type A plug) and connect a PC to the rear panel (type B plug). Using the CI-V data format and external software*, you can control the IC-7600 from a PC via the USB port. You can also transfer audio, both transmit and receive, via the USB port. * Software is not supplied from Icom.



USB (type B) connector on the rear panel



Installation example of USB keyboard

Other outstanding features

[Antenna connectors]

- Two Tx/Rx antenna connectors with automatic antenna selector
- Rx antenna In/Out connector for receiver antenna or external attenuator

[Receiver]

- General coverage receiver* covers from 30kHz to 60MHz (* Some frequency bands are not guaranteed, depending on version)
- Two types of receiver preamplifiers : Preamp 1: Increases low level signal improving intermodulation characteristics Preamp 2: High gain preamplifier
- Built-in 3-step RF attenuator (6, 12 and 18dB)

[Transmitter]

- Tx monitor • 50 CTCSS tone encoder and decoder • VOX capability (Voice operated transmission)
- All mode power control

[CW mode]

- DSP controlled CW keying waveform shaping
- Multi-function electronic keyer with adjustable keying speed, dot-dash ratio, paddle polarity and bug keyer
- CW pitch control from 300Hz to 900Hz • Double key jack
- Full break-in function and semi break-in function
- Adjustable CW envelope

Rear panel view


- | | | |
|------------------------------|------------------------|----------------------------|
| ① Ground Terminal | ⑥ ALC Input Jack | ⑪ Meter Jack |
| ② Antenna Connectors | ⑦ SEND Control Jack | ⑫ USB Connector |
| ③ DC Power Socket | ⑧ Tuner Control Socket | ⑬ CI-V Remote Control Jack |
| ④ Transverter Jack | ⑨ Accessory Sockets | ⑭ External Speaker Jack |
| ⑤ Receive Antenna Connectors | ⑩ Key Jack | |

Microphone equalizer and adjustable transmit bandwidth

The built-in audio equalizer has separate bass and treble adjustments for a total of 121 combinations, so you can adjust the tonal quality of your voice as you want. In addition, the transmit bandwidth is selectable from 100, 200, 300, 500Hz at the low-pass edge, and 2500, 2700, 2800, 2900Hz at the high-pass edge, respectively. Three types of high and low combinations can be stored in the memory as favorite settings. With this flexibility of DSP-based waveform shaping, transmit audio quality is adjustable to your preference.

High power final amplifiers

High-power FET transistors, RD100HHF1, are used in the PA unit providing excellent signal quality and low IMD characteristics. With a large heat sink and cooling fans, reliable 100W output at high duty cycle can be used, for example in contesting or data modes.



High power FET Transistors

Two types of send relay settings

For amplifier keying (SEND jack), you can select either a mechanical relay (max. 16V/500mA) or a FET switch (max. 250V/200mA). The FET switch is designed to key older tube-type amplifiers that may have high voltage on the SEND line.

Built-in high-speed automatic antenna tuner

The antenna tuner memorizes its settings based on your transmit frequency, so that it can rapidly tune when you change bands. High-voltage capacitors allow continuous-duty-cycle full-power operation.

[Operation]

- Digital meter indicates output power, ALC level, SWR, COMP (compression level), Id (drain current of the final amplifier) and Vd (voltage of the final amplifier)
- Built-in voice synthesizer announces the frequency, mode and S-meter level in English.
- Set mode function for flexible and speedy setting
- Memory pad stores up to 5 or 10 operating frequencies
- Quick split function and frequency lock function • Single knob control from RF gain to squelch
- RIT and delta Tx variable up to ± 9.999 kHz • Two clocks to show local and UTC time
- 1Hz pitch tuning and indication • 101 memories with 10-character name
- Program, memory, select memory and Δf scans • Auto tuning step function
- Adjustable tuning dial tension • Dial lock • Band edge beep (Can be disabled)
- AH-4 control circuit • Automatic tuning speed for data mode operation
- CI-V interface with optional CT-17 • Screen saver function



SPECIFICATIONS

GENERAL

- Frequency coverage :
 - U.S.A. version (#02)
 - Rx 0.030– 60.000MHz*1
 - Tx 1.800– 1.999MHz 3.500– 3.999MHz
 - 5.3305, 5.3465, 5.3665, 5.3715, 5.4035MHz*2
 - 7.000– 7.300MHz 10.100– 10.150MHz
 - 14.000– 14.350MHz 18.068– 18.168MHz
 - 21.000– 21.450MHz 24.890– 24.990MHz
 - 28.000– 29.700MHz 50.000– 54.000MHz
 - Europe (#03), Europe-1 (#04) versions
 - Rx 0.030– 60.000MHz*1
 - Tx 1.810– 1.999MHz*1 3.500– 3.800MHz
 - 7.000– 7.100MHz (Europe version only)
 - 7.000– 7.200MHz (Europe-1 version only)
 - 10.100– 10.150MHz 14.000– 14.350MHz
 - 18.068– 18.168MHz 21.000– 21.450MHz
 - 24.890– 24.990MHz 28.000– 29.700MHz
 - 50.000– 52.000MHz
- *1 Some frequency bands are not guaranteed. *2 USB mode only.
- Modes : LSB, USB, CW, RTTY, PSK31, AM, FM
- No. of memory channels : 101 (99 regular, 2 scan edges)
- Antenna impedance : 50Ω unbalanced (Tuner off)
- Antenna connector : SO-239x2 and RCA x 1 (RX only)
- Power supply requirement : 13.8V DC $\pm$ 15%
- Operating temp. range : 0 to +50°C; +32 to +122°F
- Frequency stability : Less than $\pm$ 0.5ppm (0°C to +50°C)
- Frequency resolution : 1Hz (minimum)
- Current drain :
 - Rx Stand-by 3.0A
 - Max. audio 3.5A
 - Tx Max. power 23A
- Dimensions (WxHxD) : 340x116x279.3 mm; (projections not included) 13 3/8 x 4 5/16 x 11 in
- Weight : 10kg; 22.0lb (approx.)

TRANSMITTER

- Output power :
 - SSB, CW, FM, RTTY, PSK31 2–100W
 - AM 1–30W
- Modulation system :
 - SSB Digital PSN modulation
 - FM Digital phase modulation
 - AM Digital low power modulation
- Spurious emissions :
 - HF bands Less than –50dB
 - 50MHz bands Less than –63dB
- Carrier suppression : More than 40dB
- Unwanted sideband suppression : More than 55dB
- Microphone impedance : 600Ω (8-pin connector)

RECEIVER

- Receiver system : Double conversion superheterodyne
- Intermediate frequencies :
 - 1st 64.455MHz
 - 2nd 36kHz
- Sensitivity (typical) :
 - SSB, CW 1.8– 29.995MHz 0.15μV*1
 - (BW=2.4kHz, at 10dB S/N) 50– 54.0MHz 0.12μV*2
 - AM 0.1– 1.8MHz 6.3μV*1
 - (BW=6kHz, at 10dB S/N) 1.8– 29.995MHz 2.0μV*1
 - 50– 54.0MHz 1.6μV*2
 - FM 28– 29.7MHz 0.5μV*1
 - (BW=15kHz, at 12dB SINAD) 50– 54.0MHz 0.3μV*2
- *1 Preamp-1: ON *2 Preamp-2: ON
- Squelch sensitivity (preamp: ON, threshold):
 - SSB Less than 3.2μV
 - FM Less than 0.3μV
- Selectivity (filter shape: sharp):
 - SSB (BW:2.4kHz) More than 2.4kHz/–6dB
 - Less than 3.8kHz/–60dB

- CW (BW:500Hz) More than 500Hz/–6dB
- Less than 900Hz/–60dB
- RTTY (BW:350Hz) More than 350Hz/–6dB
- Less than 650Hz/–60dB
- AM (BW:6kHz) More than 6.0kHz/–6dB
- Less than 15kHz/–60dB
- More than 12kHz/–6dB
- Less than 20kHz/–60dB
- Spurious and image rejection ratio : More than 70dB
- (Except 50MHz IF through point)
- Audio output power : More than 2.0W
- at 10% distortion with an 8Ω load
- RIT variable range : $\pm$ 9.999kHz
- PHONES connector : 3-conductor 6.35 (d) mm (1/4")
- External SP connector : 2-conductor 3.5 (d) mm (1/8") /8Ω

ANTENNA TUNER

- Matching range :
 - HF bands 16.7Ω to 150Ω unbalanced*1
 - 50MHz band 20Ω to 125Ω unbalanced*2
- *1 Less than VSWR 3:1 *2 Less than VSWR 2.5:1
- Minimum operating power :
 - HF bands 8W
 - 50MHz band 15W
- Tuning accuracy : VSWR 1.5:1 or less
- (Motor stopped)
- Insertion loss : Less than 1.0 dB
- (after tuning at 100W output)

SUPPLIED ACCESSORIES:

- DC power cable
- Hand microphone, HM-36
- Spare fuses
- Carrying handle, MB-121
- CW key plug

All stated specifications are subject to change without notice or obligation.

OPTIONS




IC-PW1/EURO HF+50 MHz 1 kW HF LINEAR AMPLIFIER
Covers all HF and 50 MHz bands, provides clean, stable 1 kW output. Automatic antenna tuner and compact detachable controller are standard. 2 exciter inputs are available.



AH-4 HF+50MHz AUTOMATIC ANTENNA TUNER
Covers 3.5–54 MHz with a 7m (23ft) or longer wire antenna.



AH-2b ANTENNA ELEMENT
A 2.5m long antenna element for mobile operation with the AH-4. All bands between 7–54 MHz can be matched.



CT-17 CI-V LEVEL CONVERTER
For remote transceiver control from a PC equipped with an RS-232C port.



HM-36 HAND MICROPHONE
Same as supplied with the radio.



SM-50 DESKTOP MICROPHONE
Dynamic desktop microphone. Includes [UP]/[DOWN] switches and low cut function.



SM-20 DESKTOP MICROPHONE
Electret desktop microphone. Includes [UP]/[DOWN] switches and low cut function.



PS-126 POWER SUPPLY UNIT
4-pin cable type power supply unit. Output: 13.8V DC (25A max.)



SP-23 EXTERNAL SPEAKER
4 audio filters; headphone jack; Input impedance: 8Ω; Input power: 5W Max.

The LCD display may have cosmetic imperfections that appear as tiny spots. This is not a malfunction or defect, but a normal characteristic of LCD displays. Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries.

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone: +49 (0211) 346047
Fax: +49 (0211) 333639
E-mail: info@icom-europe.com
URL: <http://www.icom-europe.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone: +44 (01227) 741741
Fax: +44 (01227) 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom France s.a.s.

Zac de la Plaine,
81-850 Sopot, ul. 3 Maja 54, Poland
Phone: +48 (58) 550 7135
Fax: +48 (58) 551 0484
E-mail: icompolksa@icompolksa.com.pl
URL: <http://www.icompolksa.com.pl>

Icom Polska

81-850 Sopot, ul. 3 Maja 54, Poland
Phone: +48 (58) 550 7135
Fax: +48 (58) 551 0484
E-mail: icompolksa@icompolksa.com.pl
URL: <http://www.icompolksa.com.pl>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding
Road, Haidian District, Beijing, 100039, China
Phone: +86 (010) 5889 5391/5392/5393
Fax: +86 (010) 5889 5395
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

Your local distributor/dealer: