


TYPE PF50™ AND PF60™ LOW-PROFILE PANEL FASTENER ASSEMBLIES

- Satisfies many functional and cosmetic requirements.
- Type PF50 with large head and Phillips recess for tool or finger operation.
- Available with six-lobe recess.
- Type PF50 (knurled cap) meets UL 508 "operator access area" requirements.
- Type PF60 (smooth cap) meets UL 1950 "tool only access area" requirements.
- Available in black.

Part Number Designation



Type PF50






Type PF60



SCRATCH
PROOF

DuraBlack™
finish



All dimensions are in inches.

	Thread Size	Type		Thread Code	Screw Length Code	A (Shank) Max.	Min. Sheet Thickness	Hole Size In Sheet + .003 -.000	C Max.	E +.015 -.005	G ±.025	H ±.008	P ±.025	T ₁ Max.	T ₂ Nom.	Driver Size	Min. Dist Hole C/L To Edge
		Knurled Cap	Smooth Cap														
UNIFIED	.112-40 (#4-40)	PF50	PF60	440	0	.030	.030	.203	.202	.406	.230	.207	.000	.340	.520	#1	.26
					1						.290		.060				
	.138-32 (#6-32)	PF50	PF60	632	0	.030	.030	.219	.218	.438	.230	.207	.000	.340	.520	#2	.28
					1						.290		.060				
	.164-32 (#8-32)	PF50	PF60	832	0	.030	.030	.250	.249	.468	.230	.217	.000	.340	.530	#2	.29
					1						.290		.060				
	.190-32 (#10-32)	PF50	PF60	032	0	.030	.030	.312	.311	.530	.230	.225	.000	.360	.530	#2	.33
					1						.290		.060				
	.250-20 (1/4-20)	PF52	PF62	0420	0	.058	.060	.375	.374	.625	.280	.246	.000	.395	.600	#2	.38
					1						.340		.060				

All dimensions are in millimeters.

	Thread Size x Pitch	Type		Thread Code	Screw Length Code	A (Shank) Max.	Min. Sheet Thickness	Hole Size In Sheet + 0.08	C Max.	E +0.4 -.13	G ±0.64	H ±0.2	P ±0.64	T ₁ Max.	T ₂ Nom.	Driver Size	Min. Dist Hole C/L To Edge
		Knurled Cap	Smooth Cap														
METRIC	M3 x 0.5	PF50	PF60	M3	0	0.77	0.8	5.5	5.48	10.3	5.84	5.26	0	8.64	13.21	#1	6.6
					1						7.37		1.52				
	M3.5 x 0.6	PF50	PF60	M3.5	0	0.77	0.8	5.56	5.54	11.1	5.84	5.26	0	8.64	13.21	#2	7.1
					1						7.37		1.52				
	M4 x 0.7	PF50	PF60	M4	0	0.77	0.8	6.4	6.38	11.9	5.84	5.51	0	8.64	13.46	#2	7.4
					1						7.37		1.52				
	M5 x 0.8	PF50	PF60	M5	0	0.77	0.8	8	7.98	13.5	5.84	5.72	0	9.15	13.46	#2	8.4
					1						7.37		1.52				
	M6 x 1	PF52	PF62	M6	0	1.47	1.5	9.5	9.48	15.9	7.11	6.25	0	10.04	15.24	#2	9.7
					1						8.64		1.52				