


TYPE PF30 LOW-PROFILE PANEL FASTENER ASSEMBLIES

- Satisfies many functional and cosmetic requirements.
- Large, slotted head for tool or finger operation.
- Low-profile design.
- Meets UL 508 "operator access area" requirements.

Part Number Designation





Patented.




**SCRATCH
PROOF**

**DuraBlack™
finish**



Diagonal knurl
identifies metric
thread sizes.



All dimensions are in inches.

UNIFIED	Thread Size	Type	Thread Code	Screw Length Code	A (Shank) Max.	Min. Sheet Thickness	Hole Size In Sheet + .003 - .000	C Max.	E ±.010	G ± .015	H ± .005	T ₁ Max.	T ₂ Nom.	Min. Dist. Hole C/L To Edge
	.112-40 (#4-40)	PF30	440	30	.030	.030	.203	.202	.406	.300	.202	.325	.595	.26
		PF31			.038	.040								
		PF32			.058	.060								
	.138-32 (#6-32)	PF30 ^{NS}	632	30	.030	.030	.219	.218	.438	.300	.202	.325	.595	.28
		PF31			.038	.040								
		PF32			.058	.060								
	.164-32 (#8-32)	PF30 ^{NS}	832	30	.030	.030	.250	.249	.468	.300	.207	.330	.600	.29
		PF31			.038	.040								
		PF32			.058	.060								
	.190-32 (#10-32)	PF30 ^{NS}	032	30	.030	.030	.312	.311	.530	.300	.220	.335	.605	.33
		PF31			.038	.040								
		PF32			.058	.060								
	.250-20 (1/4-20)	PF32	0420	35	.058	.060	.375	.374	.625	.350	.242	.385	.675	.38

All dimensions are in millimeters.

METRIC	Thread Size x Pitch	Type	Thread Code	Screw Length Code	A (Shank) Max.	Min. Sheet Thickness	Hole Size In Sheet + 0.08	C Max.	E ±0.25	G ± 0.4	H ± 0.13	T ₁ Max.	T ₂ Nom.	Min. Dist. Hole C/L To Edge
	M3 x 0.5	PF31 ^{NS}	M3	30	0.97	1	5.5	5.48	10.31	7.62	5.13	8.26	15.11	6.6
		PF32			1.48	1.5								
	M4 x 0.7	PF31	M4	30	0.97	1	6.4	6.38	11.89	7.62	5.26	8.38	15.24	7.37
		PF32			1.48	1.5								
	M5 x 0.8	PF31	M5	30	0.97	1	8	7.98	13.46	7.62	5.59	8.51	15.37	8.38
		PF32			1.48	1.5								
	M6 x 1	PF32 ^{NS}	M6	35	1.48	1.5	9.5	9.48	15.88	8.89	6.12	9.78	17.15	9.65

NS Not Stocked, available on special order.