

50 Ω BNC Video Patch Panel - DC bis 1.5 GHz

GVP 1x16 A 1/1 BNC50

GVP 2x16 A 1/2 BNC50

19", 1 HE, 16(32)-Kanal, Bestückt mit BNC 50 Ohm Durchgangsbuchsen



GVP 1x16 A 1/1 BNC50 ws

19", 1HE

677.110.070.19



GVP 1x22 A 1/1 BNC50

GVP 2x22 A 1/2 BNC50



GVP 2x22 A 1/1 BNC50 ws

19", 2HE

677.110.073.19



BNC – Patchkabel, 60 cm 50 Ohm



GVK 60 BNC50 sw

Electrical Data

Impedance	50 Ω	
Interface frequency max.	4 GHz	
Frequency range	DC to 1.5 GHz	1.5 to 4 GHz
Return loss	≥ 30 dB	≥ 14 dB

Mechanical Data

Number of matings	500
Weight	0.0176 kg

Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts (BNC)

Centre contact
Outer contact
Body
Insulator
Gasket

Material

Copper Beryllium Alloy
Brass
Brass
PFA / PTFE
NR

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Piece Parts (BNC)

Centre contact
Outer contact
Body
Insulator
Gasket

Material

Copper Beryllium Alloy
Brass
Brass
PFA / PTFE
NR

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating