



Fixed Resistors Selection Guide

April 1997

Let's make things better.

Philips
Components



PHILIPS

FIXED RESISTORS - QUICK SELECTION

Commodity / Professional Resistors							
Size (SMD: inch leaded: mm) Tolerance	SMD					Leaded	
	Thick film					Metal film	
	1206	0805	0603	0402	Array 0603 x 4	2.5x6.5	1.7x3.2
5%, 2% standard	RC01	RC11	RC21	RC31	ARC241	SFR25	SFR16
1% precision	-	RC02H	RC12H	RC22H	RC32H	ARC242	
	TC50	RC02G	RC12G			MRS25	MRS16S

Power Resistors								
P _{nom} at 70 °C	SMD		Leaded					
	Thick film	Thin film	Wirewound			Stand up	Radial mount	Metal film
	5, 1%	5, 1%	5%	1%	5%		5%	
	PRC	PRC	AC (40 °C)	WR	PAC (25 °C)	SMW SMF	RMW RMF	PR
1 Watt	201	202	01		01			01
2 Watt					02	02		02
3 Watt			03		03	03	03	03
4 Watt			04	0617	04			
5 Watt			05		05	05	05	
6 Watt					06			
7 Watt			07	0825			07	
10 Watt			10				10	
11 Watt				0842				
15 Watt			15					
17 Watt				0865				
20 Watt			20					

High / Ultra High-Precision Resistors						
Size SMD: inch, TC Size leaded: mm, TC	High precision			Ultra-high precision		
	0.5%	0.25%	0.1%	0.05%	0.02%	0.01%
SMD	1206	TC50	RC03G			
		TC25			MPC01	
	0805	TC50	RC13G			
		TC25			MPC11	
leaded	2.4 x 6.5	TC25	MPR24 (0.25 W)		MPR24 (0.125 W)	
		TC15				
		TC10				
		TC5				
	3.1 x 10.5	TC25	MPR34 (0.4 W)		MPR34 (0.25 W)	
		TC15				
		TC10				
		TC5				

Application Specific Resistors		
	SMD	Leaded
High ohmic/ High voltage		VR25
		VR37
		VR68
Low ohmic	LRC01	
Fusible (non flammable)	FRC01	NFR25
		NFR25H
Military		MR24 C/D/E
		MR25
		MR34 C/D/E
		MR30
		MR54 C/D/E MR52
Trimnable	RC02TR	

FIXED RESISTORS - RANGE OVERVIEW

Technology	Application	Type	Tol. (%)	Resistance range (Ω)	Temperature coefficient ($\times 10^{-6}/K$)	Maximum voltage or power (V)/(W)	Dimensions L \times W \times H D \times L (mm)	R _{th} (K/W)	Max. body temp. (°C)	E series	Basic specifications
Surface Mount Chip Resistors											
Thick Film	Standard	RC01	5; 2	1 - 4.7 5.1 - 10 M	$\leq \pm 250$ $\leq \pm 200$	200/0.25	3.2 \times 1.6 \times 0.6	200		24	IEC 115-8 55/155/56
		RC11				150/0.125	2.0 \times 1.25 \times 0.6	250			
		RC21				50/0.063	1.6 \times 0.8 \times 0.45	400			
		RC31				50/0.063	1.0 \times 0.5 \times 0.35	-			
	Precision	RC02H	1	1 - 4.99 5.1 - 9.76 10 - 1 M 1.02 M - 10 M	$\leq \pm 250$ $\leq \pm 200$ $\leq \pm 100$ $\leq \pm 200$	200/0.25	3.2 \times 1.6 \times 0.6	200		24/96	IEC 115-8 55/155/56
		RC12H				150/0.125	2.0 \times 1.25 \times 0.6	250			
		RC22H				50/0.063	1.6 \times 0.8 \times 0.45	400			
		RC32H				50/0.063	1.0 \times 0.5 \times 0.35	-			
	Precision TC50	RC02G	1	100 - 1 M	$\leq \pm 50$	200/0.25	3.2 \times 1.6 \times 0.6	200		24/96	IEC 115-8 55/125/56
		RC12G				150/0.125	2.0 \times 1.25 \times 0.6	250			
	High precision	RC03G	0.5	100 - 1 M	$\leq \pm 50$	200/0.125	3.2 \times 1.6 \times 0.6	200		24/96	IEC 115-8 55/125/56
		RC13G				150/0.1	2.0 \times 1.25 \times 0.6	250			
	Application specific	RC02TR trimmable	+0/-20 or +0/-30	1 - 4.99 5.1 - 97.6 100 - 1 M	$\leq \pm 250$ $\leq \pm 200$ $\leq \pm 100$	200/0.25	3.2 \times 1.6 \times 0.6	200		24	IEC 115-8 55/155/56
		LRC01 low ohmic	5	0.051 - 0.075 0.082 - 0.091 0.1 - 0.147 0.15 - 0.392 0.40 - 0.91	$\leq \pm 2000$ $\leq \pm 1500$ $\leq \pm 1000$ $\leq \pm 700$ $\leq \pm 250$	0.25	3.2 \times 1.6 \times 0.6	200		24	IEC 115-8 55/125/56
		FRC01 fusible									
PRC201 power		5; 1	0.020 - 0.033 0.033 - 0.056 0.062 - 0.18 0.20 - 0.91 1.0 - 9.1 10 - 1 M	$\leq \pm 2000$ $\leq \pm 1000$ $\leq \pm 700$ $\leq \pm 250$ $\leq \pm 200$ $\leq \pm 100$	200/1	3.2 \times 4.6 \times 0.6	80		24	IEC 115-8 55/155/56	
Thin Film	PRC202 power, pulse resistant										5; 1
High precision	MPC01	0.1	10 - 100 k	$\leq \pm 25$	100/0.125	3.2 \times 1.6 \times 0.6	170		all	IEC 115-8 55/125/56	
	MPC11		14 - 30 k		100/0.1	2.0 \times 1.25 \times 0.6	250				
Surface Mount Chip Resistor Array											
Thick Film	0603 x 4	ARC241	5	10 - 1 M	$\leq \pm 200$	50/0.063	3.2 \times 1.6 \times 0.6			24	IEC 115-8 55/125/56
		ARC242	1	10 - 1 M	$\leq \pm 100$						

Metal Film Resistors												
Metal Film	Standard	SFR16	5	1 - 4.7 4.75 - 100 k 102 k - 3 M	≤±250 ≤±100 ≤±250	200/0.5	1.7 × 3.2	170	155	24	IEC 115-1 55/155/56	
		SFR25 SFR25H	5	1 - 1 M 1.02 M - 10 M	≤±100 ≤±250	250/0.4 350/0.5	2.5 × 6.5	200 150	155	24		
	Precision	MRS16S	1	4.99 - 1 M	≤±50	200/0.4	1.7 × 3.2	170	155	24/96		IEC 115-1 CECC 40101
		MRS25		1 - 10 M		350/0.6	2.5 × 6.5	150	155			
		MR52		4.99 - 1 M		500/1	5.2 × 16.5	110	155			
	High precision	MR25 MR30	0.5	1 - 1 M	≤±50	250/0.4	2.5 × 6.5	240	155	192		IEC 115-1 CECC 40101
		350/0.5				3.0 × 10	200	155				
	Ultra-high precision	MPR24	0.5; 0.25; 0.1 0.05; 0.02; 0.01	4.99 - 1 M 24 - 100 k	5 - 25	250/0.25 250/0.125	2.5 × 6.5	240		all		CECC 40300 MIL-R-10509 MIL-R-55182 DIN 44061 IEC 115-5
		MPR34	0.5; 0.25; 0.1 0.05; 0.02; 0.01	4.99 - 1 M 24 - 100 k	5 - 25	350/0.4 350/0.25	3.0 × 10	200				
	Metal Film Application Specific Types	Power	PR01	5, 2, 1	0.22 - 0.976 1 - 1 M	≤±250	350/0.6 350/1	2.5 × 6.5	135	205		24
PR02			0.33 - 0.976 1 - 1 M		500/1.2 500/2		3.9 × 10	75	215			
PR03			0.68 - 0.976 1 - 1 M		750/1.6 750/3		5.2 × 16.7	60	250			
Military		MR24D	1	10 - 1 M	≤±100	200/0.125	2.4 × 6.5	240		96	MIL-R-10509- F	
		MR34D				300/0.25	3.1 × 10.5	200				
		MR54D				350/0.5	5.2 × 16.5	110				
		MR24C	1; 0.5; 0.25; 0.1	49.9 - 1 M	≤±50	200/0.1	2.4 × 6.5	240		192		
		MR34C				250/0.125	3.1 × 10.5	200				
		MR54C				300/0.25	5.2 × 16.5	110				
		MR24E				200/0.1	2.4 × 6.5	240				
		MR34E				250/0.125	3.1 × 10.5	200				
MR54E		300/0.25	5.2 × 16.5	110								
Fusible (non flammable)		NFR25	5	1 - 15 16 - 15 k	≤±200 ≤±100	250/0.33	2.5 × 6.5	240	155	24	IEC 115-1	
	NFR25H	1 - 4.7 5.1 - 15 k		≤±200 ≤±100	350/0.5	150		155				

High Ohmic/High Voltage Resistors											
Metal Glaze Application Specific	High ohmic/ High voltage	VR25	10; 5; 1	100 k - 22 M	≤±200	1600(DC), 1150(RMS)/0.25 W	2.5 × 6.5	200	155	24/96	IEC 115-1B
		VR37	5; 1	100 k - 33 M		3500(DC), 2500(RMS)/0.5 W	4.0 × 9.0	120	155		
		VR68	5; 1	100 k - 68 M		10000(DC), 7000(RMS)/1 W	6.8 × 18	70	155		

Wirewound Resistors

Cemented Wirewound	Power (standard)	AC01	5	0.1 - 9.1 10 - 1.5 k	+600 -80/+140	1 W	4.3 × 10	140	350	24	IEC115-1 40/200/56
		AC03		0.1 - 9.1 10 - 3 k	+600 -80/+140	3 W	5.5 × 13	90			
		AC04		0.1 - 9.1 10 - 6.8 k	+600 -80/+140	4 W	5.5 × 17	72			
		AC05		0.1 - 9.1 10 - 8.2 k	+600 -80/+140	5 W	7.5 × 17	52			
		AC07		0.1 - 9.1 10 - 15 k	+600 -80/+140	7 W	7.5 × 25	42			
		AC10		0.68 - 9.1 10 - 15 k	+600 -80/+140	10 W	8 × 44	32			
		AC15		0.82 - 9.1 10 - 22 k	+600 -80/+140	15 W	10 × 51	21			
		AC20		1.2 - 9.1 10 - 33 k	+600 -80/+140	20 W	10 × 67	16			
Precision Wirewound	Power (precision)	PAC01	1	0.22 - 2.2 k	±100	1 W	4.3 × 10	140	275	24	IEC115-1 55/200/56
		PAC02		0.10 - 3.6 k		2 W	5.5 × 13	90			
		PAC03		0.10 - 4.7 k		3 W	5.5 × 17	72			
		PAC04		0.10 - 8.2 k		4 W	7.5 × 17	52			
		PAC05		0.68 - 10 k		5 W	7.5 × 23	43			
		PAC06		0.68 - 12 k		6 W	7.5 × 25	42			
		Stand-up Wirewound Metal film		Power (standard)		SMW02	5	0.1 - 9.1 10 - 200			
SMF02	220 - 47 k		≤±250								
SMW03	0.1 - 9.1 10 - 560		+600 -80/+140		350/3	12 × 8 × 25		30			
SMF03	560 - 47 k		≤±250								
SMW05	0.1 - 9.1 10 - 560		+600 -80/+140		600/5	13 × 9 × 25.5		22			
SMF05	560 - 47 k		≤±250								
Radial Mount Wirewound Metal film	Power (standard)	RMW03	10 10; 5	0.22 - 1 1.1 - 3.9 k	≤±600 ≤±200	3 W	24 × 9 × 9	43	275	24	IEC115-1 25/155/56
		RMF03	5	100 - 39 k	≤±200						
		RMW05	10 10; 5	0.47 - 1 1.1 - 4.7 k	≤±600 ≤±200	5 W	27 × 9.5 × 9.5	32			
		RMF05	5	100 - 51 k	≤±200						
		RMW07	10 10; 5	0.68 - 1 1.1 - 7.5 k	≤±600 ≤±200	7 W	35 × 9.5 × 9.5	29			
		RMF07	10	1 - 100 k	≤±200						
		RMW10	10 5	1.0 - 1.5 1.6 - 10 k	≤±200	10 W	48 × 9.5 × 9.5	23			
		RMF10	10	1 - 150 k	≤±200						
Enamelled Wirewound	Power (durable coating)	WR0617E WR0825E WR0842E WR0865E	5	4.7 - 4.7 k 6.8 - 27 k 10 - 56 k 15 - 100 k	-80/+140	4 W 7 W 11 W 17 W	6 × 17 8 × 26 8 × 44 8 × 67	110 100 50 33	400	24	IEC115-1 55/200/56

Philips Components - a worldwide company

- Argentina:** Ierod, BUENOS AIRES,
Tel. (01) 786 7635, Fax. (01) 786 9397.
- Australia:** Philips Components Pty Ltd, NORTH RYDE,
Tel. (02) 9805 4455, Fax. (02) 9805 4466.
- Austria:** Österreichische Philips Industrie GmbH, WIEN,
Tel. (01) 601 01 12 41, Fax. (01) 60 101 12 11.
- Belarus:** Philips Office Belarus, MINSK,
Tel. (5172) 200 915, Fax. (5172) 200 773.
- Benelux:** Philips Nederland B.V., EINDHOVEN, NL.,
Tel. (+31 40) 2783 749, Fax. (+31 40) 2788 399.
- Brazil:** Philips Components, SÃO PAULO,
Tel. (011) 821 2333, Fax. (011) 829 1849.
- Canada:** Philips Electronics Ltd., SCARBOROUGH,
Tel. (0416) 292 5161, Fax. (0416) 754 6248.
- China:** Philips Company, SHANGHAI,
Tel. (021) 6485 0600, Fax. (021) 6485 5615.
- Colombia:** Iprelenso Ltda, SANTAFE DE BOGOTA,
Tel. (01) 345 8713, Fax. (01) 345 8712
- Denmark:** Philips Components A/S, COPENHAGEN S,
Tel. (32) 883 333, Fax. (31) 571 949.
- Finland:** Philips Components, ESPOO,
Tel. 9 (0)-615 800, Fax. 9 (0)-615 80510
- France:** Philips Composants, SURESNES,
Tel. (01) 4099 6161, Fax. (01) 4099 6427.
- Germany:** Philips Components GmbH, HAMBURG,
Tel. (040) 2489-0, Fax. (040) 2489 1400.
- Greece:** Philips Hellas S.A., TAVROS,
Tel. (01) 4894 339/(01) 4894 239, Fax. (01) 4814 240.
- Hong Kong:** Philips Hong Kong, KOWLOON,
Tel. 2784 3000, Fax. 2784 3003.
- India:** Philips India Ltd., BOMBAY,
Tel. (022) 4938 541, Fax. (022) 4938 722.
- Indonesia:** P.T. Philips Development Corp., JAKARTA,
Tel. (021) 520 1122, Fax. (021) 520 5189.
- Ireland:** Philips Electronics (Ireland) Ltd., DUBLIN,
Tel. (01) 76 40 203, Fax. (01) 76 40 210
- Israel:** Rapac Electronics Ltd., TEL AVIV,
Tel. (03) 6450 444, Fax. (03) 6491 007.
- Italy:** Philips Components S.r.l., MILANO,
Tel. (02) 6752 2531, Fax. (02) 6752 2557.
- Japan:** Philips Japan Ltd., TOKYO,
Tel. (03) 3740 5028, Fax. (03) 3740 0580
- Korea (Republic of):** Philips Electronics (Korea) Ltd., SEOUL,
Tel. (02) 709 -1472, Fax. (02) 709 1480.
- Malaysia:** Philips Malaysia SDN Berhad
Components Division, PULAU PINANG,
Tel. (04) 657 0055, Fax. (04) 656 5951.
- Mexico:** Philips Components, EL PASO, U.S.A.,
Tel. (915) 772 4020, Fax. (915) 772 4332.
- New Zealand:** Philips New Zealand Ltd., AUCKLAND,
Tel. (09) 849 4160, Fax. (09) 849 7811.
- Norway:** Norsk A/S Philips, OSLO,
Tel. (22) 74 8000, Fax. (22) 74 8341.
- Pakistan:** Philips Electrical Industries of Pakistan Ltd., KARACHI,
Tel. (021) 587 4641-49, Fax. (021) 577 035/587 4546.
- Philippines:** Philips Semiconductors Philippines Inc., METRO MANILA,
Tel. (02) 816 6380, Fax. (02) 817 3474.
- Poland:** Philips Poland Sp. z.o.o., WARSZAWA,
Tel. (022) 612 2594, Fax. (022) 612 2327.
- Portugal:** Philips Portuguesa S.A.,
Philips Components: LINDA-A-VELHA,
Tel. (01) 416 3160/416 3333, Fax. (01) 416 3174/416 3366.
- Russia:** Philips Russia, MOSCOW,
Tel. (095) 247 9124, Fax. (095) 247 9132.
- Singapore:** Philips Singapore Pte Ltd., SINGAPORE,
Tel. 350 2000, Fax. 355 1758.
- South Africa:** S.A. Philips Pty Ltd., JOHANNESBURG,
Tel. (011) 470 5911, Fax. (011) 470 5494.
- Spain:** Philips Components, BARCELONA,
Tel. (93) 301 63 12, Fax. (93) 301 42 43.
- Sweden:** Philips Components AB, STOCKHOLM,
Tel. (+46) 8 632 2000, Fax. (+46) 8 632 2745.
- Switzerland:** Philips Components AG, ZÜRICH,
Tel. (01) 488 22 11, Fax. (01) 481 77 30.
- Taiwan:** Philips Taiwan Ltd., TAIPEI,
Tel. (02) 388 7666, Fax. (02) 382 4382.
- Thailand:** Philips Electronics (Thailand) Ltd., BANGKOK,
Tel. (02) 745 4090, Fax. (02) 398 0793.
- Turkey:** Türk Philips Ticaret A.S., GÜLTEPE/ISTANBUL,
Tel. (0212) 279 2770, Fax. (0212) 282 6707.
- Ukraine:** Philips Ukraine Ltd., KIEV,
Tel. (044) 268 7327, Fax. (044) 268 6323.
- United Kingdom:** Philips Components Ltd., DORKING,
Tel. (01306) 512 000, Fax. (01306) 512 345.
- United States:**
- Philips Components, JUPITER, FL,
Tel. (561) 745 3300, Fax. (561) 745 3600.
 - For literature: (800) 447 3762.
 - Display and Wire Wound Components, ANN ARBOR, MI,
Tel. (313) 996 9400, Fax. (313) 761 2776.
 - Magnetic Products, SAUGERTIES, NY,
Tel. (914) 246 2811, Fax. (914) 246 0487.
- Uruguay:** Philips Components, MONTEVIDEO,
Tel. (02) 704 044, Fax. (02) 920 601.
- For all other countries apply to:** Philips Components,
Marketing Communications, BAE-1, P.O. Box 218, 5600 MD EINDHOVEN,
The Netherlands, Fax. +31-40-2724 547.

COB11

© Philips Electronics N.V. 1997

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.
The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

9398 237 46011

Date of release: 04/97

Let's make things better.

Philips
Components



PHILIPS