

Secondary Internal Lead-Wires for Intelcom Services



<http://www.casa.co.nz>

Edition: 10/07/2022

Type: **RLM6-PE5MM-14AWG-0M16-RED(RP1)**

General Data

Description: Battery lead RED 14AWG (2.5mm²), 320mm long with 1 x M6 + 1 x M8 pre-insulated crimp lugs at ends

Brand: CASA (OEM = TBA)

Model: RLM6-RLM8-14AWG-0M32-RED(R1)

BOM:
1 x H4127-Utilux Blue Pre-Insulated Crimp Ring-Lug M6 (1/4") hole for 2.5mm² cable...
...or... H3127

Various short lengths, 160~300mm 2.5mm² (14AWG) RED and BLACK hook-Up wire.

OPTION:
Fit bootlace ferrule to all 5mm prepared ends.

Weight: xx gms

M6 Ring Lug

H4127-Utilux or
H3127-Utilux or

H4227



5mm Strip

(pre-pepared end)



Optional
Bootlace Ferrule
2.5mm² BLF3 or
H2278 Utilux

2.5mm²
(14AWG)

Cut to Schedule (cut length)

Schedule of Lengths

48 off RLM6-PE-14AWG-0m16-Red(RP1)
24 off RLM6-PE-14AWG-0m16-Blk(BP1)
24 off RLM6-PE-14AWG-0m22-Red(RP2)
24 off RLM6-PE-14AWG-0m18-Blk(BP2)
24 off RLM6-PE-14AWG-0m30-Red(RP3o)
24 off RLM6-PE-14AWG-0m18-Red(RP3i)
24 off RLM6-PE-14AWG-0m22-Blk(BP3)

DRAFT

NOTICE – the information on this page is not guaranteed for accuracy – CASA accepts no responsibility (neither expressed nor implied) for any errors or the consequence therefrom.