



0.6/2.8 AF

Video Cable 75 Ω



Application

Video cables are primary used in closed circuit TV systems and in several studio applications for transmission of image signals.

Standards

For analogue and digital video signals (Composite, component, SDI, SDV, SDTI, HDTV)

Flame resistance

PVC: IEC 60332-1

FRNC: IEC 60332-1, IEC 60754, IEC 61034

FRNC-C: additionally IEC 60332-3 C

Construction

Inner conductor	solid copper wire, bare, diameter 0.6 mm
Insulation	Foam-PE, diameter 2.8 mm
Outer conductor	Al-PETP-Al-foil under tinned copper braid, diameter 3.4 mm
Sheath	FRNC or PVC, diameter 4.5 mm green, RAL 6018
Printing	for FRNC: DRAKA COMTEQ - 0.6/2.8 AF - 75 Ω $\pm$ 1% - HDTV FRNC for PVC: DRAKA COMTEQ - 0.6/2.8 AF - 75 Ω $\pm$ 1% - HDTV

Electrical properties

at 20°C

DC resistance	Inner conductor	61 Ω /km
	Outer conductor	17 Ω /km
Mutual capacitance		56 pF/m
Characteristic impedance		75 Ω $\pm$ 0.75 Ω
Velocity ratio		78 %
Screening factor		> 100 dB



0.6/2.8 AF

Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)	
1	1.2	50 – 300	≥ 26
3	1.9	300 – 3000	≥ 22
5	2.5	3000 – 3500	≥ 18
10	3.5	3500 – 5000	≥ 15
30	5.9		
100	10.5		
200	15.0		
300	18.7		
500	24.5		
800	31.5		
1000	35.3		
1500	43.2		
2250	54.0		
3000	63.6		
3500	70.7		
4000	76.3		
4500	82.2		
5000	88.1		

Technical data

Product code	Type	Weight kg/km	Standard delivery length m	Drum size KTG/ring	Copper content	Tensile force N	Bending radius mm	Storage
1002160 CT2738600	0.6/2.8 AF PVC green	27	1000	051	14	60	25	inside
1002161 CT2738601	0.6/2.8 AF PVC black	27	1000	051	14	60	25	inside
1002162 CT2738602	0.6/2.8 AF PVC blue	27	1000	051	14	60	25	inside
1002164 CT2738604	0.6/2.8 AF PVC violett	27	1000	051	14	60	25	inside
1002166 CT2738609	0.6/2.8 AF PVC black + special marking	27	1000	051	14	60	25	inside
1002167 CT2738610	0.6/2.8 AF PVC green + meter marking	27	1000	051	14	60	25	inside
1002203 CT2850202	0.6/2.8 AF FRNC-C gn	28	1000	051	14	60	25	inside
1002204 CT2850207	0.6/2.8 AF FRNC-C yel.	28	1000	051	14	60	25	inside
1002205 CT2850208	0.6/2.8 AF FRNC-C blue	28	1000	051	14	60	25	inside



Draka

Draka Comteq | Cable Solutions – EMEA

st13e.doc
16.08.2006
page 3 of 3

0.6/2.8 AF