



8218 Coax - Standard Analog Video Cable - 75 Ohm Miniature Coax



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

27 AWG stranded (7x35) .017" bare copper-covered steel conductor, polyethylene insulation, 93% tinned copper braid shield, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
AWG	27
Stranding	7x35
Conductor Diameter	.017 in.
Conductor Material	BCCS - Bare Copper Covered Steel

INSULATION:

Insulation Material	PE - Polyethylene
Insulation Diameter	.100 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	TC - Tinned Copper
Outer Shield % Coverage	93 %

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.150 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +60°C
UL Temperature Rating	60°C (UL AWM Style 1354)
Bulk Cable Weight	14 lbs/1000 ft.
Max. Recommended Pulling Tension	32 lbs.
Min. Bend Radius (Install)	2 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:



8218 Coax - Standard Analog Video Cable - 75 Ohm Miniature Coax

APPLICABLE STANDARDS:

AWM Specification	UL Style 1354 (30 V 60°C)
-------------------	---------------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	.115 µH/ft
Nom. Capacitance Conductor to Shield	20.5 pF/ft
Nominal Velocity of Propagation	66 %
Nominal Delay	1.54 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	120 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	5.7 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			1.2
	10			2.4
	50			4.2
	100			5.7
	200			8.3
	400			12.1
	700			16.5
	900			19.0
	1000			20.0

Max. Operating Voltage - UL 30 V RMS (UL AWM Style 1354)

Max. Operating Voltage - Non-UL 1700 V RMS

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8218 0101000	75 OHM COAX	1000	16	BLACK	C
8218 010500	75 OHM COAX	500	8	BLACK	
8218 010U1000	75 OHM COAX	U1000	16	BLACK	
8218 010U500	75 OHM COAX	U500	8.5	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-22-2004



8218 Coax - Standard Analog Video Cable - 75 Ohm Miniature Coax

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.