


9259 Coax - Standard Analog Video Cable - 75 Ohm Coax



For more information please
call
1-800-Belden1

[See Put-ups and Colors](#)

Description:

22 AWG stranded (7x30) .030" bare copper conductor, foam polyethylene insulation, 95% bare copper braid shield, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	59/U
AWG	22
Stranding	7x30
Conductor Diameter	.030 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	FPE - Foam Polyethylene
Insulation Diameter	.146 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	BC - Bare Copper
Outer Shield % Coverage	95 %

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.241 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
Non-UL Temperature Rating	80°C
Bulk Cable Weight	33 lbs/1000 ft.
Max. Recommended Pulling Tension	65 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

9259 Coax - Standard Analog Video Cable - 75 Ohm Coax

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	UL Style 1354 (30 V 80°C)

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

SUITABILITY:

Suitability - Indoor	Y
Suitability - Outdoor	Y

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	89259 or 82259

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	.09 µH/ft
Nom. Capacitance Conductor to Shield	17.3 pF/ft
Nominal Velocity of Propagation	78 %
Nominal Delay	1.3 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	15 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	2.6 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.30
	5			.65
	10			.90
	50			2.1
	100			3.0
	200			4.5
	400			6.6
	700			8.9
	900			10.1
	1000			10.9

Max. Operating Voltage - UL	300 V RMS
-----------------------------	-----------

NOTES:

Notes	For CCTV Applications.
-------	------------------------

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
------	-------------	--------------	--------------------	--------------	-------

9259 Coax - Standard Analog Video Cable - 75 Ohm Coax

9259 010100	#22 PE RG 59/U TYPE	100	4.1	BLACK	
9259 0101000	#22 PE RG 59/U TYPE	1000	37	BLACK	C
9259 010500	#22 PE RG 59/U TYPE	500	18	BLACK	C
9259 010U1000	#22 PE RG 59/U TYPE	U1000	36	BLACK	
9259 010U500	#22 PE RG 59/U TYPE	U500	18.5	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 01-30-2004

© 2004 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.