


## MINIMAL SECTION PREMISE OPTICAL CABLE - TECHNICAL DATASHEET

### FL@TCORE™



Drawing not to scale.

### Cable description / Application

Indoor drop optical fibre cable with steel wire reinforcement and LSOH sheath.

Designed to run from the distribution point to the subscriber, in both home and business premises.

### Approvals

Approved for use in the Chorus network.

### Behaviour in flame and fire

Flame resistant

### Temperature range

Installation: -5 °C -> +60 °C

Transport & Storage: -40 °C -> +70 °C

Operation: -5 °C -> +60 °C

### Minimum bending radius

Dynamic: 30 mm

Static: 15 mm

### Cable construction

Number of Fibres: 2

Fibre type: G657A2

Strength member: 2 x 0.5 mm coated steel wires

Cable size (height x width in mm): 1.7 (±0.15) x 2.9 (±0.15)

Cable Weight (kg/km): 9

Max installation tension (N): 150

Sheath material: LSOH

Sheath Colour: White

### Identification

Sheath Marking: Printed at 1 metre intervals as below:

PRYSMIAN xxxxx 2 FO BBXS DROP CABLE \*\*\*\*M

Where xxxxx = batch number

Fibre identification:

Fibre 1	Fibre 2
Blue	Orange

### Packaging

500 m length packs easy to dispense with our "Reel in a box" technology.

### Main Characteristics

Test	Standard	Value	Sanction*
Maximum Tension at installation (short term)	IEC 60794-1-2-E1	150 N	$\Delta\alpha \leq 0.1$ dB, No damage to the jacket
Crush	IEC 60794-1-2-E3	1000 N / 100 mm	$\Delta\alpha \leq 0.1$ dB, No damage to the jacket
Temperature range	IEC 60794-1-2-F1	-5 -> +60 °C	$\Delta\alpha \leq 0.2$ dB / km

\* Values for single-mode fibres, all optical measurements performed at 1550 nm.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

